The original and first coly TER WELL REPORT filed with the JUN 16 1969

Well No. /N/4W-5

	State Well No
STATE ENGINEER, SALEM, OREGON 97310	. E.
STATE ENGINEER, SALEM OREGON 97310 (Please type or print) within 30 days from be date (Please type or print) (Please type or print)	***
of well completion with F. h.C. The Completion of the line of the	State Permit No.
of well completion.	1
1/6/11 owned by Dwayne Heikes (500)	

TOTTI CONES DI OWAYNE THEIRES	<u> </u>			
(1) OWNER:	(11) LOCATION OF WELL:			
Name Halbert Clapshaw	County Washington Driller's well number			
Address Rte 2 Box 367 Forest Grove, Ore	5 1-N 4-W			
				W.M .
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivis	ion corner		1 7
New Well 🚰 Deepening 🗌 Reconditioning 🗍 Abandon 🗍				
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(10) 11171 1 1 0 0			
Rotary X Driven Domestic Industrial Municipal Domestic	(12) WELL LOG: Diameter of well			inch
Cable Jetted Johnestic & Industrial Municipal Description Test Well Other	Depth drilled 300 ft. Depth of com	pleted well	1.300	ft.
	Formation: Describe color, texture, grain size	and struc	ture of r	naterials;
(5) CASING INSTALLED: Threaded Welded W	and show thickness and nature of each stra with at least one entry for each change of for	num and a mation. R	quiier pe eport eac	netrated, h change
8 "Diam from 0 ft to 121 ft Gage 1 wall	in position of Static Water Level as drilling p	roceeds. N	Note drilli	ng rates.
" Diam. from ft. to ft. Gage	MATERIAL	From	То	swL
" Diam. from ft. to ft. Gage	Top Soil	0	2	
PERFORATIONS: Perforated? Yes No.	Yellow clay	2	TO	
Type of perforator used	Red clay	10	15	
Size of perforations in. by in.	Brown clay	15	25	
	Red clay	25	40	
perforations from	Brown clay	40	95	
perforations from	Brown sandstone	95	120	
perforations from	Soft brown rock	120	150	
perforations from	Red lava	150	160	·
periorations from the first to	Blue med. rock	160	175	<u> </u>
(7) SCREENS: Well screen installed? ☐ Yes 🍒 No	Soft Brown rock	175	180	·
Manufacturer's Name	Blue hard rock	180	200 255	<u> </u>
Type Model No.	Black lava	200 255	265	··
Diam. Slot size Set from ft. to ft.	Grey rock	265	290	
Diam. Slot size Set from ft. to ft.	Blue rock Brown rock soft	290	300	·
(8) WATER LEVEL: Completed well.	Brown Pock Solt	230	000	
ft. below land surface Date 6-6-69				
Arresian pressure lbs. per square inch Date		•		
(9) WELL TESTS: Drawdown is amount water level is				
lowered below static level				· · · · · · · · · · · · · · · · · · ·
Was a pump test made? 🗌 Yes 🏅 No If yes, by whom?				
d: gal./min. with ft. drawdown after hrs.	Work started 6-4-69 19 Comple		6-69	19
" " "	Date well drilling machine moved off of well	6-6-6	9	19
" " " " " " " " " " " " " " " " " " "	Drilling Machine Operator's Certification	:		
Bailer test 300 gal./min. with 165tt. drawdown after 2 hrs.	This well was constructed under my			
Artesian flow g.p.m. Date	rials used and information reported about knowledge and belief.	ve are ti	rue to n	ny best
Temperature of water Was a chemical analysis made? ☐ Yes ¥ No	[Signed] Martin Breet	. Date 6	-12	, 19 <i>6 J</i>
(10) CONSTRUCTION:	((Drilling Machine Operator)			/
Well seal-Material usedCement	Drilling Machine Operator's License No.	566		
Depth of seal 120 feet	Water Well Contractor's Certification:			
Diameter of well bore to bottom of seal 12 in.	This well was drilled under my jurisdiction and this report is			
Were any loose strata cemented off? Yes 15 No Depth	true to the best of my knowledge and bel	ief.		•
Was a drive shoe used? Yes A No	NAME Ralph Turner Drill	ing Cc		
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type	or print)	
Type of water? depth of strata	Address Rte 1 Box 141 Hi	llsbor	0, 01	egon
Method of sealing strata off	R-DAM	- 6 s		
	[Signed] (Water Well Contri		······································	•••••
Was well gravel packed? ☐ Yes No Size of gravel:		/ s =	ラ	10
Gravel placed from ft. to ft.	Contractor's License No247 Date &	`	<u></u> ,	19