

NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON
within 30 days from the date of well completion.

RECEIVED OCT 29 1970
RECEIVED DEC - 8 1970
STATE OF OREGON
STATE ENGINEER SALEM, OREGON

WASH 0678
IN/4W-1970

(1) OWNER:
Name Delbert Evers
Address Rt. 1 Forest Grove, Oregon 97116

(2) TYPE OF WORK (check):
New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) PROPOSED USE (check):
Rotary Driven Domestic Industrial Municipal
Cable Jetted Irrigation Test Well Other
Dug Bored

CASING INSTALLED:
6" Diam. from 0 ft. to 522 ft. Gage 1/4
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:
Perforated? Yes No.
Type of perforator used
Size of perforations in. by in.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.
..... perforations from ft. to ft.

(7) SCREENS: Well screen installed? Yes No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.
Static level ft. below land surface Date
Artesian pressure 17 lbs. per square inch Date 10-14-70

(9) WELL TESTS: Drawdown is amount water level is lowered below static level.
Was a pump test made? Yes No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " " "
" " " " "
Bailer test 60 gal./min. with 0 ft. drawdown after 1 hrs.
Artesian flow 60 g.p.m. Date October 14, 1970
Temperature of water 54 Was a chemical analysis made? Yes No

(10) CONSTRUCTION:
Well seal—Material used Bentonite (Cement)
Depth of seal 510 ft.
Diameter of well bore to bottom of seal 12 in.
Were any loose strata cemented off? Yes No Depth
Was a drive shoe used? Yes No
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(11) LOCATION OF WELL:
County Washington Driller's well number
1/4 1/4 Section 15 T. 1N R. 4W W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 595 ft. Depth of completed well 595 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

MATERIAL	From	To	SWL
Top soil	0	4	
Sandy			
Brown clay	4	25	
hard			
Quick Sand	25	60	
Gray			
Light Brown	60	80	
Clay			
Gray Clay	80	100	
Soft			
Blue Clay	100	155	
soft			
Sand and wood	155	175	
Gray clay	175	185	
hard			
Sand, wood	185	200	
Dark Clay	200	260	
Hard			
Brown Clay	260	300	
Hard			
Red Clay	300	335	
hard			
Rock	335	345	
Soft			
Red Clay	345	450	
Brown Clay	450	510	
Rock	510	595	
Soft			
Cement	510	530	
Water	529	595	

Work started 09-09 1970 Completed October 15 1970
Date well drilling machine moved off of well October 15 1970

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Cyril Vandehy Date 10-15, 1970
(Drilling Machine Operator)

Drilling Machine Operator's License No. 42

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
NAME Cyril Vandehy (Type or print)
(Person, firm or corporation) (Type or print)
Address Rt. 2 Box 262 Forest Grove, Oregon 97116
[Signed] Cyril Vandehy (Water Well Contractor)
353
Contractor's License No. Date October 15, 1970