NOTICE TO WATER WELL CONTRACTOR TO FINE WATER WELL REPORT SEP 14 1967

WATER WELL REPORT SEP 14 1967

WATER WELL REPORT SEP 14 1967

state engineer, salem, oregon 27310 TE ENGINEERS type or print TE ENGINEERS within 30 days from the date of well completion.

(1) OWNER:	(11) LOCATION OF WELL:		
Name Melvin Love	County Washington Driller's well number		
Address Rt. 1. Forest Grove, Oregon	¼ ¼ Section 14 T.1N	R.4W	W. M .
	Bearing and distance from section or subdivision	n corner	
(2) TYPE OF WORK (check):			
New Well Deepening Reconditioning Abandon	- •	-	-
If abandonment, describe material and procedure in Item 12.		····	····
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well h	oelow casing	6#
Rotary Driven Domestic Manicipal Municipal Domestic Manicipal Domestic Manicipal Domestic Manicipal Domestic Do	Depth drilled 500 ft. Depth of compl		500 ft.
Dug	Formation: Describe color, texture, grain size		
CASING INSTALLED: Threaded Welded Welded Gage Gage	and show thickness and nature of each stratu with at least one entry for each change of form in position of Static Water Level as drilling pro	m and aquif ation. Repor	fer penetrated, rt each change
The state of the state o	MATERIAL	From	To SWL
ft. to ft. Gage	Brown Silty	0	10
PERFORATIONS: Perforated? Yes No.			
Type of perforator used	Brown Clay	10	25
Size of perforations in. by in.			
	Blue Quick Sand	25	65
perforations from ft. to ft.			
perforations fromft. toft.	Gray Clay Soft	65	80
perforations from ft. to ft.	THE A SUMMED IN CO. A	80	120
perforations from ft. to ft.	Wood in Quick Sand	00	
(7) SCREENS: Well screen installed? Yes Y No	Blue Clay and Fine Sand	120	220
Manufacturer's Name	Plus Clert	220	230
Type Model No.	Blue Clay	J.J.	
Diam. Slot size Set from ft. to ft.	Brown Clay	230	245
Diam. Slot size Set from ft. to ft.			
(8) WATER LEVEL: Completed well.	Blue Clay	245	320
Static level ft. below land surface Date			
ian pressure 35 lbs. per square inch Date 8/15/67	Red Rock and Gravel	320	340_
(9) WELL TESTS. Drawdown is amount water level is		710	/30
lowered below static level	Red Clay Soft Red Rock Soft	340 410	<u>410</u> 500
Was a pump test made? ☐ Yes WNo If yes, by whom?	Work started 7/29 1967 Complet		
Yield: gal./min. with ft. drawdown after hrs.	Date well drilling machine moved off of well	8/1	
" "		0/1	5 2007
" " "	Drilling Machine Operator's Certification: This well was constructed under my di	most superi	ricion Moto
Bailer test gal./min. with ft. drawdown after hrs.	rials used and information reported above	rect superv	to my best
Artesian flow 12 g.p.m. Date 8/15/67	knowledge and belief.	, ,	
Temperature of water 54 Was a chemical analysis made? ☐ Yes M No	[Signed] Orilling Machine Operator)	pate 8/10	6 <u>, 19</u> 67
(10) CONSTRUCTION:	Drilling Machine Operator's License No	12	
Well seal—Material used Bentanite	Drilling Machine Operator's License No		
Depth of seal ft.	Water Well Contractor's Certification:		
Diameter of well bore to bottom of seal10 in.	This well was drilled under my jurisdi		this report is
Were any loose strata cemented off? Yes No Depth	true to the best of my knowledge and belie		
Was a drive shoe used? ☐ Yes X No	NAME Cyril Vandehey (Person, firm or corporation)	(Type or	print)
Did any strata contain unusable water? Yes No	Address Rt.2. Box 262 For	est Grov	e. Oregon
Type of water? depth of strata	a (1)	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	
Method of sealing strata off	[Signed] Cynt Vaydihl	y	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contra		
Gravel placed from ft. to ft.	Contractor's License No353 Date	8/16	<u> 19.67</u> .