## NOTICE TO WATER WELL CONTRACTOR

The original and first copy
of this report are to be
filed with the

## O CO EWATER WELL REPORT

OCT U STATE OF OREGON

WASH 6 100

State Well No. /N/4w / 14 N

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

CREGON

(Please type or print)

OREGON

G-4535

State Permit No.

(1) OWNER:	(11) LOCATION OF WELL:			
Name Kenneth Willis	1 ' '	il number		
Address Rt. 1, Box 296 Forest Grove, Ore.	County Washington Driller's we		Δ¥	W.M.
Address Res 1, Box 270 Polest Grove, Ore.		Z		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdi	vision corner		
New Well 🚻 Deepening 🗌 Reconditioning 🗍 Abandon 🗀				
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(19) THEFT LOC.		<i>j</i> -	
Rotary Driven Domestic Maintenant Municipal Domestic Maintenant Municipal Domestic D	(12) WELL LOG: Diameter of w		_	
Dug	Depth drilled 539 ft. Depth of co	mpleted wel	<sup>1</sup> 539	ft.
CASING INSTALLED: Threaded   Welded	Formation: Describe color, texture, grain and show thickness and nature of each st			
CASING INSTALLED: Threaded Welded W	with at least one entry for each change of	formation. R	Report each	h change
"Diam from ft. to ft. Gage ft. Gage ft. Gage	in position of Static Water Level as drilling	1	T	
" Diam. fromft. toft. Gage	MATERIAL	From	То	SWL
	Brown Silty	0	30	
PERFORATIONS: Perforated?   Yes No.				
Type of perforator used	Shot Soil Red	30	70_	
Size of perforations in. by in.	Coet Glow Pod	ma	7.00	
perforations from ft. to ft.	Soft Clay Red	70	100	
ft. to ft.	Soft Clay Grav	100	120	
perforations from ft. to ft.		±. EUU	العدا	
perforations from ft. toft.	Soft Clay Red	120	420	
perforations from ft. to ft.				
(7) SCREENS: Well screen installed?   Yes No	Clay Block	420	425	
Manufacturer's Name			,	· 
Type Model No.	Clay Red	425	455	
Diam Slot size Set from ft. to ft.				
Diam. Slot size Set from ft. to ft.	Rock Soft	455	539	
(8) WATER LEVEL: Completed well.				
Static level ft. below land surface Date		****		
20. NOISY TAILE BULLEC DATE			<del> </del>	
9/29/01				
(9) WELL TESTS: Drawdown is amount water level is lowered below static level	***			
Was a pump test made? ☐ Yes ☑ No If yes, by whom?			<u>                                     </u>	
Yield: gal./min. with ft. drawdown after hrs.	Work started 9/14 19 67 Com		/29	<sup>19</sup> 67
" " "	Date well drilling machine moved off of wel	1 9	/29	19 67
n " " " "	Drilling Machine Operator's Certificati	on:		
Bailer test gal./min. with ft. drawdown after hrs.	This well was constructed under m			
Artesian flow 42 g.p.m. Date 9/29/67	rials used and information reported a knowledge and belief.	above are t	true to r	ny best
77 - 77	[Signed] CHINA	Mypate	10/3	1067
	(Drilling Machine Operator)	pare	40.Se.f. A.J	, 10524
(10) CONSTRUCTION:	Drilling Machine Operator's License N	6 42		
Well seal—Material usedBentanite				
Depth of sealft.	Water Well Contractor's Certification:			
Diameter of well bore to bottom of sealin.	This well was drilled under my justifue to the best of my knowledge and		nd this r	eport is
Were any loose strata cemented off? Yes No Depth	NAME Curil Vondahav			
Was a drive shoe used? Yes No	(Person, firm or corporation)	(Tyr	e or print)	
Did any strata contain unusable water?  Yes No	Address Rt.2, Box 262 For	rest Gro	ve. Or	agon
Type of water? depth of strata	1 1/2/	11	,	O
Method of sealing strata off	[Signed] CMW Uand	hly		
Was well gravel packed?   Yes TNo Size of gravel:	(Water Well Co			
Gravel placed from ft. to ft.	Contractor's License No353 Date	9/29	,	1967