WWC Number 1266

18 R	ECEIVED	2-1	1	12	1 /
STATE OF OREGON (WASH)	11111 - 100F	_< </td <td>W/</td> <td><u>ر ک</u></td> <td>16</td>	W/	<u>ر ک</u>	16
WATER SUPPLY WELL REPORT \ \ \ \ \ \ \ \ \ \ \ \ \ \	JUN - 2 1995	/ `	_ (
(as required by ORS 537.765) NATE	RESOURCES DEPT	(START CARD)#_	79221		
Instructions for completing this report are on the last page of this form. S	,		 		
(1) OWNER: Well Number #3-95	(9) LOCATION OF W				
Name LOEN NURSERY Address 18710 SW PACIFIC DR	CountyWASHINGTON Latitude Longitude				
GITEDIA OD OD OTIVO	Township 2S Section 21	N or S Range_		E or V	v. wm.
City SHERWOOD State OR Zip 97140 (2) TYPE OF WORK		SW 1/4 bt Block		1/4 odivision	
X New Well Deepening Alteration (repair/recondition) Abandonment		(or nearest address) 18			C DR.
(3) DRILL METHOD:	SHOOT NOTE OF WALL	· —	ERWOOD,		<u> </u>
Rotary Air Rotary Mud Cable Auger	(10) STATIC WATER				
Other	16 ft. below land surface. Date 05/25/95				25/95
(4) PROPOSED USE:	Artesian pressurelb. per square inch. Date				
Domestic Community Industrial Irrigation	(11) WATER BEARIN	NG ZONES:			
Thermal Injection Livestock Other					
(5) BORE HOLE CONSTRUCTION:	Depth at which water was	first found 50			
Special Construction approval Yes No Depth of Completed Well 95 ft. Explosives used Yes No Type Amount	From	То	Ectimated	Flow Rate	SWL
HOLE SEAL	50	90	24 G		16
Diameter From To Material From To Sacks or pounds			2-7 0.	L 1.1	1-0
10 0 95 Bentonite 0 25 18 sks.	}	`			
Filter pack 25 95 32 sks.					
	(12) WELL LOG:				
How was seal placed: Method A B C D E	,	Elevation			
X Other poured into dry annular			T		T
Backfill placed from ft. to ft. Material	Materia	<u> </u>	From	To	SWL
Gravel placed from 25 ft. to 95 ft. Size of gravel 1-C SAND	Topsoil		0	<u> </u>	
(6) CASING/LINER:	Brown sandy cl Coarse-fine br			19	
Diameter From To Gauge Steel Plastic Welded Threaded Casing: 6" +1 50 200HSI X X	grave	-	a 4	19	
Casing: 6" +1 50 200FSI X X — — — — — — — — — — — — — — — — —	Fine gray sand		1 19	46	<u> </u>
8" +1 5 .250 X	Sticky gray cl	•	46	50	
	Soft gray sand		50	65	16
Liner:	Gray-black san		65	75	11
	Gray-brown san		75	90	16
Final location of shoe(s)	Sticky gray cl	ay	90	95	
(7) PERFORATIONS/SCREENS:					ļ
Perforations Method					<u> </u>
X Screens Type SLOTTED Material PVC Slot Tele/pipe					
From To size Number Diameter size Casing Liner				ļ	-
50 90 .020 6" PIPE X					
		4, 4, 4,			
				<u> </u>	<u> </u>
(8) WELLTESTS: Minimum testing time is 1 hour		4/95 Comp		25/95	
Flowing	(unbonded) Water Well				
Pump Antesian Artesian	I certify that the work lof this well is in complian	performed on the cons	truction, alter	ation, or aba	andonment tandards.
Yleld gal/min Drawdown Drill stem at Time	Materials used and inform	ation reported above ar	e true to the b	est of my k	nowledge
24 79 1 hr+	and belief.	_	WWW NE	obor 11	.02
	Signed Mol.	Right	WWC Nur	nber <u>14</u> Date <u>05/</u>	
Temperature of water 53 F Depth Artesian Flow Found	(bonded) Water Well Co	nstrugor Octification		U3/	20/93
Was a water analysis done? Yes By whom	I accept responsibility	for the construction, alt	eration, or aba	indonment	work
Did any strata contain water not suitable for intended use? Too little	performed on this well du performed during this tim	ring the construction da	tes reported a	bove. All v	vork
Salty Muddy Odor Colored Other	construction standards. T	his report is true to the l	oregon water sest of my kno	owledge and	d belief.
Depth of strate:		_ ,)	WWC Nur	_	

Signed

Depth of strata: