WASH 69015

RECEIVED

STATE OF OREGON WATER SUPPLY WELL REPORT (as required by ORS 537.765 & OAR 690-205-0210)

AUG 0 3 2010

WELL LABEL # L	103933

WATER RESOURCES DEPT START CARD # | 206112 SALEM, OREGO (1) LAND OWNER Owner Well I.D. (9) LOCATION OF WELL (legal description) First Name Robert Last Name Jossy County WASHING Twp I N N/S Range 3 E/W WM 1/4 of the NW Company Jossy Farms 1/4 Tax Lot 1901 Sec 12 NW 31965 NW Beach Rd. Address Tax Map Number Hillsboro State OR Zip 97124 City DMS or DD Lat " or DMS or DD (2) TYPE OF WORK New Well Deepening Conversion Nearest address Street address of well Alteration (repair/recondition) Abandonment 31965 NW Beach Rd. (3) DRILL METHOD Rotary Air Rotary Mud Cable Auger Cable Mud (10) STATIC WATER LEVEL Date Reverse Rotary Other SWL(psi) SWL(ft) Existing Well / Predeepening (4) PROPOSED USE Domestic Irrigation Community Completed Well 07-23-2010 Industrial/ Commercial Livestock Dewatering Flowing Artesian? Thermal Injection Other WATER BEARING ZONES Depth water was first found 163 (5) BORE HOLE CONSTRUCTION Special Standard Attach copy SWL Date Est Flow SWL(psi) SWL(ft) From 07-23-2010 174 Depth of Completed Well _180 42 **BORE HOLE SEAL** sacks Dia From Material From To Amt lbs 10 0 180 Bentonite 0 20 27 S 20 140 35 S Cement 6.75 180 554 180 Concrete 554 4 (11) WELL LOG Ground Elevation How was seal placed: Method XC From To Brown silty clay 0 22 XOther Pour into annular 22 37 Gray silty clay Backfill placed from ft. to Material Sticky gray clay 37 49 Filter pack from 140 ft. to 180 ft. Material Sand Size 1C Soft red-brown sandy clay 49 62 Explosives used: Yes Type Amount Sticky gray-brown clay 62 73 (6) CASING/LINER Casing Liner Dia Sticky red-brown clay 73 117 Sticky gray clay 117 153 From Gauge Stl Plstc Wld Thrd To 163 Soft brown clay 153 X sdr21 ◉ 160 6 Medium to coarse brown sand 163 166 (• × 175 180 sdr21 Soft gray clay 166 169 **(** ₹ X 1.5 5 •250 174 169 Fine gray sand 199 Sticky blue-gray clay 174 202 Medium to coarse brown sand 199 Shoe Inside Outside Other 249 Location of shoe(s) Sticky blue-gray clay 202 277 Soft gray sandy clay 249 Temp casing Yes Dia From 277 286 Sticky brown clay (7) PERFORATIONS/SCREENS Sticky blue-gray clay 286 330 Perforations Method Soft dark gray clay 330 348 Screens Type Slotted Material PVC Fine black sand with clay 362 Perf/S Casing/ Screen # of Tele/ Scrn/slot Slot Date Started 07-07-2010 Completed 07-23-2010 creen Liner slots To width length pipe size From Screen Casing 175 PIPE 6 160 .020 (unbonded) Water Well Constructor Certification I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my knowledge and belief. (8) WELL TESTS: Minimum testing time is 1 hour License Number Password: (if filing electronically) Flowing Artesian O Pump Bailer O Air Signed Yield gal/min Drawdown Drill stem/Pump depth Duration (hr) 12 (bonded) Water Well Constructor Certification

I accept responsibility for the construction, deepening, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.

License Number	1266	Date 07-	23-2010	
Password : (if filir	g electronically)			•
Signed		ZBUUL		
Contact Info (option	origit)			
				_

Amount

°F Lab analysis Yes By

Yes (describe below)

Description

Temperature 55

From

Water quality concerns?

WASH 69015

WATER SUPPLY WELL REPORT - continuation page

WELL I.D. # L	103933
START CARD	# 206112

Comments/Remarks Comments/Re	(5) BORE HOLE CONSTRUCTION						10) STATIC V	WATER	LEVEL				_				
Swild Swil			HOLE_			SEAI	_		sacks/	1			LEVEL				
### From To Material Size Comments/Remarks	Dia	Fron	n To		Material	From	To	Amt				ig Lones					
(6) CASING/LINER Casing Liner Dia + From To Gauge Sti Piste Wild Thrd Shieky red clay 484 489 1800 Shieky red clay 480 1800 Shiek		-							+	1	SWL Date F	From	To	Est Flow	SWL(psi)	+ SWL(ft)	
(6) CASING/LINER Casing Liner Dia + From To Gauge Sti Piste Wild Thrd Shieky red clay 484 489 1800 Shieky red clay 480 1800 Shiek		┼	_	 -} }				+-	╀┈┤	1							
(6) CASING/LINER Casing Liner Dia + From To Gauge Sti Piste Wild Thrd Shieky red clay 484 489 1800 Shieky red clay 480 1800 Shiek		+	_					+-	+	1							
(6) CASING/LINER Casing Liner Dia + From To Gauge Sti Piste Wild Thrd Shieky red clay 484 489 1800 Shieky red clay 480 1800 Shiek				— i					\vdash	1						 	
(6) CASING/LINER Casing Liner Dia + From To Gauge Sti Piste Wild Thrd Shieky red clay 484 489 1800 Shieky red clay 480 1800 Shiek										1							
(6) CASING/LINER Casing Liner Dia + From To Gauge Sti Piste Wild Thrd Shieky red clay 484 489 1800 Shieky red clay 480 1800 Shiek										1						 	
(6) CASING/LINER Casing Liner Dia + From To Gauge Sti Piste Wild Thrd Shieky red clay 484 489 1800 Shieky red clay 480 1800 Shiek										1						-	
(6) CASING/LINER Casing liner Dia + From To Gauge Sti Piste Wild Thrd Stocky red day 362 484 Wall Completed 3180 ft. Blottom bore filled with Concrete from 554 to 180 ft. (4) yds. of Concrete) (7) PERFORATIONS/SCREENS Perfis Casing/ Screen reen Liner Dia From To width length slots pipe size reen Liner Dia From To width length slots pipe size (8) WELL TESTS: Minimum testing time is 1 hour Yield gal/min Drawdown Drill stem/Fump dench Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED		FILT	ER PAG	CK)							
Casing Liner Dia + From To Gauge Sti Plstc Wild Thrd Soft gray sandy clay Sticky red clay 484 489 Sticky brown clay 485 496 Firm brown & black sandstones 496 554 Well Completed @ 180 ft Bottom bore filled with Concrete from 554 to 180 ft Gottom bore f	<u>_F</u>	rom	To	Mate	erial Siz	<u>e</u>				1						 	
Casing Liner Dia + From To Gauge Sti Plstc Wild Thrd Soft gray sandy clay Sticky red clay 484 489 Sticky brown clay 485 496 Firm brown & black sandstones 496 554 Well Completed @ 180 ft Bottom bore filled with Concrete from 554 to 180 ft Gottom bore f	L									1		-				\vdash	
Casing Liner Dia + From To Gauge Sti Plstc Wild Thrd Soft gray sandy clay Sticky red clay 484 489 Sticky brown clay 485 496 Firm brown & black sandstones 496 554 Well Completed @ 180 ft Bottom bore filled with Concrete from 554 to 180 ft Gottom bore f	L.									1							
Casing Liner Dia + From To Gauge Sti Plstc Wild Thrd Soft gray sandy clay Sticky red clay 484 489 Sticky brown clay 485 496 Firm brown & black sandstones 496 554 Well Completed @ 180 ft Bottom bore filled with Concrete from 554 to 180 ft Gottom bore f										-							-
Casing Liner Dia + From To Gauge St Pists Wild Thrd Soft gray sandy clay 362 434 Slicky trad clay 444 489 Slicky troub. Well Completed @ 180 ft. Bottom bore filled with Concrete from 554 to 180 ft. (4) yds. of Concrete) Well Completed @ 180 ft. Bottom bore filled with Concrete from 554 to 180 ft. (4) yds. of Concrete) (8) WELL TESTS: Minimum testing time is 1 hour Yield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED	(6) CA	ASINO	G/LINI	ER											F		
Slicky row clay	Casi	no Line	r Dia		From To	Gauge	Stl Diet	w W/Id	Thed	16	Soft gray sandy cla	<u>Material</u>					\neg
Slicky brown clay 489 496 554	Casi	LIII	, Dia		110111 10	- Gauge	Ou PISI	2 —	11110			-,					7
(7) PERFORATIONS/SCREENS Perf'S Casing/Screen To width length slots pipe size creen Liner Dia From To width length slots pipe size (8) WELL TESTS: Minimum testing time is 1 hour Yield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units From To Description Duration (hr) RECEIVED	\bowtie	$\leftarrow \bowtie$		}=			\mathcal{L}	\forall	Н		Sticky brown clay						7
(7) PERFORATIONS/SCREENS Perf/S Casing/Screen	\bowtie	$\leftarrow > \downarrow$		⊣⊨			$\chi \zeta$	\forall	\vdash				nes				7
(7) PERFORATIONS/SCREENS Perf/S Casing/ Screen Creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED	\bowtie	\leftarrow		⊣⊨	 		$\mathcal{L}_{\mathcal{L}}$	₩	H								7
(7) PERFORATIONS/SCREENS Perf/S Casing/ Screen Creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To width length slots pipe size creen Liner Dia From To Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED	\bowtie	$\leftarrow \bowtie$		⊣	} 		\times	♦ H-l	H	10							
(7) PERFORATIONS/SCREENS Perf/S Casing/ Screen	\succ	\sim		⊣⊨	 		\mathcal{L}		H		Well Completed @	2) 180 ft.]
(7) PERFORATIONS/SCREENS Perf/S Casing/ Screen recens Liner Dia From To width length slots pipe size (8) WELL TESTS: Minimum testing time is 1 hour Yield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED	\succ	\rightarrow		⊣ ⊨	 	- - .	\times	♦ ⊢	\vdash	1 1			crete from 554	4 to 180 ft.			_
Perf/S Casing/ Screen creen Liner Dia From To width length slots pipe size	\bowtie	\vdash		⊣⊨			\times	♦ ├─	\vdash	1 -	(4 yds. of Con	ncrete)					4
Perf/S Casing/ Screen creen Liner Dia From To width length slots pipe size	\bowtie	$\vdash \!$	 	$\dashv \vdash$	 	-	\times	\forall	\vdash	$I \vdash$							4
Perf/S Casing/ Screen creen Liner Dia From To width length slots pipe size	igcup							4 L		$I \vdash$							\dashv
Perf/S Casing/ Screen creen Liner Dia From To width length slots pipe size										十七							┨
Perf/S Casing/ Screen creen Liner Dia From To width length slots pipe size										11							+
Perf/S Casing/ Screen creen Liner Dia From To width length slots pipe size										11							1
Perf/S Casing/ Screen creen Liner Dia From To width length slots pipe size	(7) PE	RFO	RATIO	ONS/S	SCREENS					1 [٦
(8) WELL TESTS: Minimum testing time is 1 hour Yield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED						Scrn/slot	Slot	# of	Tele/]
(8) WELL TESTS: Minimum testing time is 1 hour Yield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED				Fro	m To					1 -							_
Vield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED										1 -							4
Vield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED				ļ													4
Vield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED	\vdash			ļ													4
Vield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED	\vdash			├				-		11				_			┪
Vield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED				-						11							┪
Vield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED	\vdash			-													٦
Vield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED																	
Vield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED] [
Vield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED																	1
Vield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED																	_
Vield gal/min Drawdown Drill stem/Pump depth Duration (hr) Water Quality Concerns From To Description Amount Units RECEIVED	(O) \$3/I		recte	. M:-	imauma taatis	or time is 1	h			1							
Water Quality Concerns From To Description Amount Units RECEIVED	(0) WI	CLL I	LSIS	: IATIII	ilinum testii	ig time is i	nour			1 -							_
Water Quality Concerns From To Description Amount Units RECEIVED	Yield	gal/min	Dr	awdow	n Drill ste	m/Pump depth	Du	ration (h	<u>r)</u>	1	Commonts/Da-	moules					
From To Description Amount Units RECEIVED			_						_	1	Januarits/Rei	mai K3					
From To Description Amount Units RECEIVED									-		·						٦
From To Description Amount Units RECEIVED									-								
From To Description Amount Units RECEIVED			-		_				4								
From To Description Amount Units RECEIVED									-								1
From To Description Amount Units RECEIVED																	1
RECEIVED	Wat	ter Qu	ality Co	ncern	18												
RECEIVED	Fron	n	To		Descripti	on	Amoun	t Unit	s								
RECEIVED																	
													1				1
																_	
	\vdash			_			+							REC	FIVE	J	
AUC 0 5 2010	<u> </u>			-			+							• • • • •			
														AUC	9 201		<u>_</u>