NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

filed with the

WATER WELL REPORT
STATE OF OREGON APR 2 9 1974 State Well No. 25

(1) OWNER:	(10) LOCATION OF WELL.				
Name David Parr	(10) LOCATION OF WELL: County Washington Driller's well number				
Address 19225 S. W. Pacific Highway		7	W.		
Sherwood, Oregon 9711,0	SW 14 NW 14 Section 21 T. 25	_R	¥¥ •	W.M.	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivisi	on corner			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐					
If abandonment, describe material and procedure in Item 12.					
	(11) WATER LEVEL: Completed w				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 43	6		ft.	
Rotary M Driven Domestic Industrial Municipal Domestic	Static level 15 ft. below land s	urface. I	ate	4/24/71	
Dug 🛮 Bored 🗀 Irrigation 🖂 Test Well 🗀 Other 🖂	Artesian pressure lbs. per squar	e inch. I	ate		
CASING INSTALLED: Threaded Welded 5. 6." Diam. from O. ft. to 1436. ft. Gage 250. "Diam. from ft. to ft. Gage ft. Gage Perforated? Yes 4. No. Type of perforator used	(12) WELL LOG: Diameter of well below casing 6.11 Depth drilled 470 ft. Depth of completed well 460 ft. Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.				
	MATERIAL Decem of The Toronton and T	From	To_	SWL	
Size of perforations in. by in.	Brown silty clay topsoil	0	3		
perforations from ft. to ft.	Brown sand & silt, occ. brown clay streak	3	25		
perforations from ft. to ft.	Muddy brown sand & small pea	 	رے		
perforations from ft. to ft.	gravel	25	50		
(7) SCREENS: Well screen installed? Yes X No	Blue silty clayocc. black				
Manufacturer's Name	sand streak	50	75		
Type Model No	Blue clay w/cemented gravel	75	85		
Diam ft. to ft.	Black-brown clay w/cemented				
Diam. Slot size Set from ft. to ft.	gravel streaks	85	95		
(0) WET I DECING. Drawdown is amount water level in	Sticky gray-brown clay	95	155		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Silty Gray sand	155	160		
Was a pump test made? ☐ Yes 🔼 No If yes, by whom?	Silty gray clay, occ. gravel				
Yield: gal./min. with ft. drawdown after hrs.	and sand	160	170		
" " "	Hard sticky blue clay, occ.				
" " "	gritty streak	170	190		
airlift Bailer test 100 gal./min. with 365ft. drawdown after 2 hrs.	Sticky gray & blue clay	190	275		
	Sticky brown clay, occ.gritty				
Artesian flow g.p.m.	& soft rock fragments	275	300		
perature of water Depth artesian flow encountered ft.	Work started 4/16/74 19 Complete	a 4/24	/74	19	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	4/25	/74	19	
Well seal—Material used Cement Grout with 2% bentonite	Drilling Machine Operator's Certification:			F = 30 c	
Well sealed from land surface to 436 ft. Diameter of well bore to bottom of seal 9-7/8 in. Diameter of well bore below seal in. Number of sacks of cement used in well seal 12 sacks Number of sacks of bentonite used in well seal sacks	This well was constructed under my Materials used and information reported best knowledge and belief. [Signed] (Drilling Machine Operator) Drilling Machine Operator's License No.	above ar Date	e true /25/7	to my	
Brand name of bentonite	Water Well Contractor's Certification:				
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.				
Was a drive shoe used? Yes No Plugs Size: location ft.	Name A. M. Jannsen Drilling Co	0.			
Old any strata contain unusable water? Yes No	(Person, firm or corporation)	(Тур	e or prin		
Type of water? depth of strata	Address 21075 S.W. Tualatin Vall	эу Нwу.	, Alo	na, Or.	
Method of sealing strata off Was well gravel packed? □ Yes ☑ No Size of gravel:	[Signed] Swent W.— Water Well Control	uns	e_	•	
	Contractor's License No. 79 Date	こしい			
Gravel placed from ft. to ft.	Contractor's License No	+1.42/14	t	, 19	

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

MEGEIVEU

STATE OF OREGON STATE ENGINEER

(Please type or print)

SALEN OPECOState Permit No.

(Do not write above this line) SALEM. OREGORITATE Permit No.

	i			
(1) OWNER:	(10) LOCATION OF WELL:			
Name David Parr Page 2	County Driller's well number			
Address	¼ ¼ Section T.	R.		W.M.
	Bearing and distance from section or subdivision	on corner	•	
(2) TYPE OF WORK (check):				
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon 🔣				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ell		_ _
(3) TYPE OF WELL: (4) PROPOSED USE (check):		CII.		ft.
Determ Cl. Driven Cl.	Depth at which water was first found		D-4-	IL.
Cable	Static level ft. below land surface. Date			
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per squar	e inch. I	Date	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well k	nolow co-	ing	
				ft.
ft. Gage	Formation: Describe color, texture, grain size a and show thickness and nature of each stratum	and struct m and ag	ure of n uifer pe	nateriais; netrated,
	with at least one entry for each change of forma	tion. Repo	ort each c	:hange in
) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin			
Type of perforator used	MATERIAL	From	To	swL
Size of perforations in. by in.	Hard sticky brown clay	300	350	
perforations from ft. to ft.	Blue clay w/black sand and	1250	266	
perforations from ft. to ft.	soft pea gravel	350	365	
perforations from ft. to ft.	Hard cemented blue & black	366	205	
(E) CODERNO	gravel	365	375	
(7) SCREENS: Well screen installed? Yes No	Gritty brown clay	375	395	
Manufacturer's Name	Cemented hard brown & black	205	405	
Type Model No	gravel and sand	395	405	
Diam Slot size Set from ft. to ft.	Fractured black & brown basal	T		
Diam. Slot size Set from ft. to ft.	occ. red-brown clay frag-	1.05	435	
(8) WELL TESTS: Drawdown is amount water level is	ments	405	422	
lowered below static level	Broken brown basaltsome	435	460	100 g
Was a pump test made? Yes No If yes, by whom?	gravel type fragments	455	470	
Yield: gal./min. with ft. drawdown after hrs.	Soft brown basalt	1400	410	
n n	Well completed to 460 ft			
" " "	HETT COMPTERED TO TOO TO	[
Bailer test gal./min. with ft. drawdown after hrs.				
Artesian flow g.p.m.				
perature of water Depth artesian flow encountered ft.	Work started 19 Completed 1			19
(0) CONSTRUICTION:	Date well drilling machine moved off of well			19
(9) CONSTRUCTION:	Drilling Machine Operator's Certification			
Well seal—Material used	This well was constructed under my	direct	super	vision.
Well sealed from land surface to ft.	Materials used and information reported	above	are true	e to my
Diameter of well bore to bottom of seal in.	best knowledge and belief.	50.0		40
Diameter of well bore below seal in.	[Signed](Drilling Machine Operator)	Date		, 19
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No.			
Number of sacks of bentonite used in well seal sacks				· · · · · · · · · · · · · · · · · · ·
Brand name of bentonite	Water Well Contractor's Certification:			
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd		nd this 1	report is
of water lbs./100 gals.	true to the best of my knowledge and be	lief.		
Was a drive shoe used? Yes No Plugs Size: location ft.	Name (Person, firm or corporation)	/m-	vne or pri	int)
Did any strata contain unusable water? Yes No				
Type of water? depth of strata	Address			*************
Method of sealing strata off	[Signed](Water Well Cont			
Was well gravel packed? Yes No Size of gravel:				
Gravel placed from ft. to	Contractor's License No Date			, 19