NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT CEIVED STATE OF OREGON MAR - 8 197 State Well No. 25 / W 35 de (Please type or print)

(Please type or print)

WATER RESOURCEStapermit No. ...

(Do not write above this line)

SALEM. OREGON

	ONEGON
(1) OWNER:	(10) LOCATION OF WELL:
Name C.E. Willey	County WASA. Driller's well number 548
Address 9335 SW GREENHILL LIN.	SW 4 SE 4 Section 35 T. 28 R. IW W.M.
TUALATIN, OVE.	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	
New Well Deepening Reconditioning Abandon	
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 252 ft.
Rotary 😿 Driven 🛘 Domestic 🕅 Industrial 🗎 Municipal 🗀	Static level 144 ft. below land surface. Date 2-16-7
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing 6"
" Diam. from Dea ft. to ft. Gage	Depth drilled 75 ft. Depth of completed well 275 ft.
" Diam, from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aguifer penetrated.
	with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	HAND GRAY BASA/T 200252
perforations from ft. to ft.	Brown Porcus Basa/Hunter 252 268 144
perforations from ft. to ft.	HALL GRAY BASA/7 268 275
perforations from ft. to ft.	
(7) SCREENS: Well screen installed? Yes No	
Manufacturer's Name	
Type Model No	,
Diam Slot size Set from ft. to ft.	
Diam Slot size Set from ft. to ft.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? Yes No If yes, by whom? OPera Jar	
Yield: 50 gal./min. with //O ft. drawdown after 2 hrs.	
AIR LIFT "	M. 18
" " " "	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
mperature of water 2 Depth artesian flow encounteredft.	Work started 2-16 1977 Completed 2-16 1977
(9) CONSTRUCTION:	Date well drilling machine moved off of well 2-16 19 77
Well seal—Material used	Drilling Machine Operator's Certification:
Well sealed from land surface to	This well was constructed under my direct supervision.
Diameter of well bore to bottom of sexty in.	Materials used and information reported above are true to my best knowledge and belief.
Diameter of well bore bylow East 18N1 AUG	[Signed] Saymon & Dorugate 2-17 1977
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No. 305
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of water lbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? Yes No Plugs Size: location ft.	Name MAY Borchors-Well Drilling
Did any strata contain unusable water? Yes No	Merson, firm or corporation) (Type or print)
Type of water? depth of strata	Address 1 3 Dok of 1/2 Strawwood
Method of sealing strata off	[Signed] Saymond U. Dorcher
Was well gravel packed? Yes No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. Date 2-17 1977