WASH 73639

STATE OF OREGON

WATER SUPPLY WELL REPORT

WELL I.D. LABEL# L 117224

212133

START CARD#

(as required by ORS 537.765 & OAR 690-205-0210) **ORIGINAL LOG#** (1) LAND OWNER Owner Well I.D. First Name Last Name (9) LOCATION OF WELL (legal description) Company EDWARDS MEADOWS HOMEOWNERS ASSOCIATION County WASHINGTON Twp 1 S N/S Range 2 Address PO BOX 33

City HILLSBORO SW 1/4 of the NE 1/4 Tax Lot 1400 State OR Zip <u>97123</u> Tax Map Number (2) TYPE OF WORK New Well Deepening Conversion DMS or DD Lat Alteration (complete 2a & 10) Abandonment(complete 5a) " or DMS or DD (2a) PRE-ALTERATION
Dia + From Stl Plstc Wld Thrd Street address of well Gauge Casing: 2640 SE MEADOWLARK DR. From Amt sacks/lbs Seal: (3) DRILL METHOD (10) STATIC WATER LEVEL SWL(psi) SWL(ft) Rotary Air X Rotary Mud Cable Auger Cable Mud Existing Well / Pre-Alteration Reverse Rotary Other Completed Well 05-01-2015 Domestic X Irrigation Community Flowing Artesian? Dry Hole? (4) PROPOSED USE Industrial/Commercial Livestock Dewatering Depth water was first found 85 WATER BEARING ZONES Thermal __Injection __ Other SWL Date From To Est Flow SWL(psi) + SWL(ft) (5) BORE HOLE CONSTRUCTION Special Standard (Attach copy) 05-01-2015 135 Depth of Completed Well 140 **BORE HOLE** SEAL sacks/ Dia From Material From Amt lbs 12.25 140 Bentonite 25 27 15.94 Calculated 55 14 (11) WELL LOG Calculated 10.85 Ground Elevation **X**c Method How was seal placed: Шв From Material To Xother POUR INTO ANNULAR TOPSOIL **BROWN CLAY** Backfill placed from _ ft. Material. 1 3 __ ft. to . FINE GRAY SAND/SILT 24 3 Filter pack from ____55___ ft. to ___140__ ft. Material SAND Size 1C&8 GRAY SILT WITH CLAY & WOOD 24 70 Explosives used: Yes Type_ Amount 74 DARK GRAY CLAY 70 (5a) ABANDONMENT USING UNHYDRATED BENTONITE SOFT GRAY SANDY CLAY OCC SAND SEAMS 74 98 **Pounds Pounds** AND WOOD Proposed Amount **Actual Amount** 98 SOFT GRAY CLAY 101 (6) CASING/LINER Casing Liner GRAY SANDY CLAY WITH SAND SEAMS 101 110 Dia From Gauge Tο FINE TO COARSE BLACK SAND WITH TRACE 110 .250 85 **(FINE GRAVEL** 121 135 140 .250 SOFT GRAY CLAY 121 129 FINE TO MEDIUM GRAY BROWN SAND 135 SOFT LITE GRAY CLAY 140 Inside Outside Other Location of shoe(s) Temp casing Yes Dia. From _ (7) PERFORATIONS/SCREENS Perforations Method Screens Type WIREWOUND Material STAINLESS STL Completed 05-01-2015 Date Started 04-24-2015 Perf/S Casing/ Screen Tele/ # of Scrn/slot Slot (unbonded) Water Well Constructor Certification creen Liner Dia width length slots pipe size Screen Casing PIPS I certify that the work I performed on the construction, deepening, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to the best of my knowledge and belief. License Number (8) WELL TESTS: Minimum testing time is 1 hour O Flowing Artesian O Pump Bailer O Air Yield gal/min (bonded) Water Well Constructor Certification Drawdown Drill stem/Pump depth Duration (hr) 42 I accept responsibility for the construction, deepening, alteration, or abandonment 70 work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief. °F Lab analysis Wes By _ Temperature 56 Yes (deleCENTEDS BY WASHIND DIS Water quality concerns? License Number 1266 Date 05-01-2015 Contact Info (optional) MAY 0 8 2015 ORIGINAL - WATER RESOURCES DEPARTMENT