NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED JAN 9 1974 STATE ENGINEER SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED JUL 26 1973 STATE ENGINEER SALEM OREGON

State Well No. 2S/2W-8
State Permit No.

(1) OWNER:
Name John Harrington
Address Rte 2 Box 155-A Hillsboro, Oregon

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED:
Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 225 ft. Gage 4 wall
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:
Perforated? ☐ Yes ☒ No
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
air " " "
Bailer test 60 gal./min. with 65 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Bentonite
Well sealed from land surface to 75 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal 4 sacks
Brand name of bentonite National
Number of pounds of bentonite per 100 gallons of water 50 lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Washington Driller's well number
¼ ¼ Section 8 T. 2-S R. 2-W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 45 ft.
Static level 45 ft. below land surface. Date 7-18-73
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 6
Depth drilled 325 ft. Depth of completed well 325 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Top soil	0	2	
Brown clay	2	18	
Yellow sandy clay	18	45	
Blue silt	45	126	
Black sand	126	134	
Blue clay	134	160	
Brown clay	160	210	
Brown ~~clay~~ Sandstone	210	225	
Brown med. rock	225	235	
Pink lava rock	235	265	
Blue med. rock	265	286	
Brown lava rock	226	312	
Blue med. rock	312	325	
~~200~~ 70 @ 305			
60 @ 280			
70 @ 235			
60 @ 215			

Work started 7-17-73 19 Completed 7-18-73 19
Date well drilling machine moved off of well 7-18-73 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Ralph Turner Date 7-23-73 19
(Drilling Machine Operator)
Drilling Machine Operator's License No. 254

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Ralph Turner Drilling Co.
(Person, firm or corporation) (Type or print)
Address Rte 1 Box 141 Hillsboro, Oregon
[Signed] Ralph Turner
(Water Well Contractor)
Contractor's License No. 247 Date 7-23-73, 19

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119