NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

Ŵ	185H 846	
1	846	

State Well No. ZW/4W-10 CC
State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:		
Name Coy HOWARD	County WASHINGton Driller's well number		
Address 14.33 N EVANS	SW 145 W 1/4 Section 10 T. 20 R. 4W W.M.		
MEMINNVIlle Oregon 97/128	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):			
New Well A Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 180 ft.		
Rotary K Driven Domestic Municipal Domestic Municipal Domestic Municipal Domestic No. 2012	Static level 90 ft. below land surface. Date 5-2/-79		
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐			
CASING INSTALLED: Threaded [] Welded EX	200. per square men. Date		
CASING INSTALLED: Threaded Welded Wel	(12) WELL LOG: Diameter of well below casing		
"Diam. fromft. toft. Gage	Depth drilled 203 ft. Depth of completed well 203 ft.		
"Diam. fromft. to	Formation: Describe color, texture, grain size and structure of materials;		
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in		
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.		
Type of perforator used	MATERIAL From To SWL		
Size of perforations in. by in.	top Soll 00		
perforations from ft. to ft.	Red Clay 120		
perforations from ft. to ft.	Beown Clay 20 30		
perforations from ft. to ft.	GRAY C/AY 30 40		
(7) SCREENS: Well screen installed? ☐ Yes ☑ No	BROWN Clay 40 160		
Manufacturer's Name	Can 1 to 1		
Type Model No.	Beavel Medium with		
Diam. Slot size Set from ft. to ft.	BROWN CLAY 160 203		
Diam. Slot size Set from ft. to ft.			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? Yes X No If yes, by whom?	RECEIVED		
Yield: gal./min, with ft, drawdown after hrs.			
IL test 100 Gpm From "500" "	MAY 2 9 1979		
Fretest 75 Gpm From 170 43 Gpm From 120	WATER RESOURCES DEPT.		
Bailer test gal./min. with ft, drawdown after hrs.	SALEM, OREGON		
Artesian flow g.p.m.			
perature of water 54/Depth artesian flow encounteredft.	Work started 5 - 19 19 79 Completed 5 - 21 19 79		
	Date well dellite a well-		
(9) CONSTRUCTION:	Date well drilling machine moved off of well $5 \sim 2/$ 1979		
Well seal-Material used Conent	Drilling Machine Operator's Certification:		
Well sealed from land surface to 50 ft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my		
Diameter of well bore to bottom of seal in. Diameter of well bore below seal	best knowledge and belief.		
Number of sacks of cement used in well sealsacks	[Signed] Cynd Day Machine Operator) Date 5 11, 1971		
How was cement grout placed? pumped IN	Drilling Machine Operator's License No. 42		
And the state of t	Water Well Contractor's Certification:		
	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Yes No Plugs Size: location ft.			
Oid any strata contain unusable water? 🔲 Yes 🔯 No	Name (Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address Rt 2 Dox 262 Forest Geove Dee		
Method of sealing strata off	[Signed] Cyn V an dehly		
Was well gravel packed? [] Yes [] No Size of gravel:	[Signed]		
Gravel placed from ft. to ft.	Contractor's License No. 353 Date 5 22 1979		