

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date
of well completion

RECEIVED
NOV 17 1971
STATE ENGINEER
SALEM, OREGON

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

Do not write above this line)

State Well No. 2/3W-2

State Permit No. _____

(1) OWNER:

Name D. A. Barnes
Address 174 S.E. 12th Ave Hillsboro Ore.

(2) TYPE OF WORK (check):

New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☒ Welded ☐
6" Diam. from 0 ft. to 92 ft. Gage 280
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☐ Yes ☒ No.

Type of perforator used _____

Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☒ No

Manufacturer's Name _____
Type _____ Model No. _____
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is
lowered below static level

Was a pump test made? ☐ Yes ☒ No If yes, by whom?

Yield: gal./min. with ft. drawdown after hrs.

" " " "

Baller test 20 gal./min. with 0 ft. drawdown after 1 1/2 hrs.

Artesian flow g.p.m.

Temperature of water 53 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used cement
Well sealed from land surface to 20 ft.
Diameter of well bore to bottom of seal 9 in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 2 sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite _____
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Washington Driller's well number
1/4 1/4 Section 2 T. 2 R. 3 W. W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 162 ft.
Static level 128 ft. below land surface. Date Nov 14, 71
Artesian pressure lbs. per square inch, Date

(12) WELL LOG:

Diameter of well below casing 6
Depth drilled 172 ft. Depth of completed well 172 ft.

Formation: Describe color, texture, grain size and structure of materials;
and show thickness and nature of each stratum and aquifer penetrated,
with at least one entry for each change of formation. Report each change in
position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
sand	0	2	
Red clay	2	30	
Yellow "	30	50	
hard rock soft	50	77	
Brown " "	77	91	
Blue rock	91	104	
Brown "	104	140	
Blue "	140	162	44
Black "	162	172	44

Work started Oct 26 1971 Completed Nov 11 1971
Date well drilling machine moved off of well Nov 15 1971

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision.
Materials used and information reported above are true to my
best knowledge and belief.

[Signed] E. M. Gregory Date Nov 16, 1971
(Drilling Machine Operator)

Drilling Machine Operator's License No. 207

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is
true to the best of my knowledge and belief.

Name E. M. Gregory Drilling Co.
(Person, firm or corporation) Rt. 1, Box 159

Address Banks, Oregon 97106

[Signed] E. M. Gregory (Water Well Contractor)

Contractor's License No. 99 Date Nov 16, 1971