NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

## WATER WELL REPORT

## STATE OF OREGON

- (Please type or print)

(Do not write above this line)

State Well No. 35/10-2 & a.
State Permit No.

	•
(1) OWNER:	(10) LOCATION OF WELL:
Name Earl May	County Washington Driller's well number 169
Address 7300 SW Hazel Fern Rd.	NE CE O CC 477
Tigard, Or, 97223	
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(11) YVA MVD Y VVVVV (1)
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
Rotary N Driven C	Depth at which water was first found 150 ft.
Domestic   Industrial   Municipal	Static level 102 ft. below land surface. Date  Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded T	
6 "Diam. from 0 ft. to 65 ft. Gage • 250	(12) WELL LOG: Diameter of well below casing 6!
" Diam, fromft. toft. Gage	Depth drilled 232 ft. Depth of completed well 232 ft.
ft. toft. Gage	Formation: Describe color, texture, grain size and structure of materials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
PERFORATIONS: Perforated?  Yes  No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used	MATERIAL From To SWL
Size of perforations in. by in.	Top soil 0 2
perforations from ft. to ft.	Clay, brown 2 18
perforations from ft. to ft.	Rock, black, broken 18 19
perforations from ft. to ft.	Clay, brown 19 22
(7) SCREENS: Well screen installed?   Ves. 70 No.	Rock, black, fract. 22 58
West percent unputated. [2] Yes [2] 140	Rock, black 58 142
Manufacturer's Name  Type Model No	<u>Cinders, red</u> 142 147
Diam. Slot size Set from ft. to ft.	Rock, black 147 150
Diam. Slot size Set from ft. to ft.	*Rock, black, fract. 150 172
Det Holli	Basalt, gray 172 186
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	*Rock, black, fract. 186 208 Basalt, gray 208 232
a pump test made? X Yes I No If yes, by whom? Driller	DEOERGE
rid: 60 gal./min. with 4 ft. drawdown after 3 hrs.	TEUEIVED
" " "	CED 3 7 1000
" " " "	SEP 15 1980
Eailer test gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT
	SALEM, OREGON
perature of water Depth artesian flow encountered ft.	Work started 8-27 19 80 Completed 8-30 1980
(9) CONSTRUCTION:	Date well drilling machine moved off of well 8-30 1980
C t-	
	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.
Well sealed from land surface to	Materials used and information reported above are true to my
Diameter of well bore below seal	best knowledge and belief.
Number of realistic form	[Signed] Sur Plus Date 9-7, 19 80
How was cement grout placed? Pressure grouted from	Drilling Machine Operator's License No. 994
65 ft. to land surface.	Water Well Contractor's Certification:
	This well was drilled under my jurisdiction and this report is
Was a drive shoe used?   Yes X No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water?  Yes No	Name B & G Drilling
Type of water? depth of strata	(Person, firm or corporation) (Type or print)  Address 10030 S. Macksburg Rd. Canby, Or.
Method of sealing strata off	
	[Signed] Little & Wallettall
Was well gravel packed? ☐ Yes ▼ No Size of gravel:	(Water Well Contractor)
Gravel placed from ft. to ft.	Contractor's License No. 637 Date 9-7 , 1980