NOTICE TO WATER WELL CONTRACTOR The original and first copy

of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 9 3100 within 30 days from the date of well completion.

WATER WELL REPORT STATE OF OREGON

(Please type or print)

JUL ? 1 197 State Permit No. 35/1W 2 66

(Do not write above this line)
WATER RESOURCES DEPT.

(1) OWNER:	(10) LOCATION OF WEEL:		
Name Lee Thompson	County Washington Driller's well number 38-76		
Address 74130 SW Grahams Ferry Rd.	NW % NW % Section 2 T. 3S R. 1W W.M.		
Sherwood, OR	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	7		
New Well XX Deepening □ Reconditioning □ Abandon □			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	1 7		
Rotary XX Driven [1	Depth at which water was first found 139 ft.		
Cable	Static level 86 ft. below land s	urface. Date 7-9-76	
Dug ☐ Bored ☐ Irrigation Test Well ☐ Other ☐	Artesian pressure Ibs. per square inch. Date		
CASING INSTALLED: "Diam. from +2 ft. to 54 ft. Gage 25 ft. Gage 7 Diam. from ft. to ft. Gage 7 Diam. from ft. to ft. Gage 7 PERFORATIONS: Perforated? Yes XXO.	(12) WELL LOG: Diameter of well below casing		
Type of perforator used	MATERIAL	From To SWL	
Size of perforations in. by in.	Clay brown	0 18	
perforations from ft. to ft.	Basalt brown soft	18 45	
perforations from ft. to ft.	black	45 93	
perforations from ft. to ft.	<u>" red</u>	93 96	
(7) SCREENS: Well screen installed? Ves XV No.	grey	96 122	
To an action and action action and action action and action action and action action action action action action action and action actio	" black hard	122 139	
Manufacturer's Name	" black broken 40gr		
Diam. Slot size Set from ft. to ft.	DIACK	149 191	
Diam. Slot size Set from ft. to ft.	black broken	191 203	
	" black	203 209 209 209 211	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	<u>" red soft</u> " black	209 211 211 223	
Was a pump test made? ₩xes □ No If yes, by whom? Driller	" black broken	223 265 77	
Yield: 150 gal./min. with 284 ft. drawdown after 2 hrs.	" black hard	265 315	
	" black crev. 120 gpm	315 316 86	
130 104	" black hard	316 324	
	" green soft	324 337	
Bailer test gal./min. with ft. drawdown after hrs.	" black crev.	337 345	
Artesian flow g.p.m.	" black hard	345 370	
nperature of water Depth artesian flow encountered ft.	Work started 6-29 19 76 Complete	ed 7-9 196	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7 - 9 ₁₉ 76	
Well seal—Material used Cement and Bentonite Well sealed from land surface to 53 ft.	Drilling Machine Operator's Certification: This well was constructed under my direct supervision.		
Diameter of well bore to bottom of seal11 in.	Materials used and information reported above are true to my best knowledge and belief.		
Diameter of well bore below sealin.	[Signed] / Date 7-14 197.6.		
Number of sacks of cement used in well seal5 sacks	(Drilling Machine Operator)		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.	***************************************	
Brand name of bentonite Baroid	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons of water	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? Tyes XNo Plugs Size: location ft.	Name Skyles Drilling and Supply (Person, firm or corporation) (Type or print)		
Did any strata contain unusable water? Yes XXVo	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 1169 Molalla Ave.	oregon City, OR	
Method of sealing strata off	[Signed] Maria Dillay Con		
Was well gravel packed? ☐ Yes ★No Size of gravel:	(Water Well Contractor)		
Gravel placed from ft. to ft.	Contractor's License No. 553 Date 7-14 , 1976		