NOTICE TO WATER WELL CONTRACTOR

1W-31 dab

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the	LL REPORT WASH	1/1W-31 da		
STATE ENGINEER, SALEM OREGON 97310 (Please tyles) within 30 days from the date of well completion.	FOREGON 009162 State Well No. peror print) G-4248	To		
(1) OWNER:	(11) LOCATION OF WELL:			
Compre Manuskain Maken District de				
% Carter, Bringle & Associates	County Washington Driller's well n			
Oregon Bank, Building, Portland, Oregon	¼ ¼ Section 31 T. 1	$S_{R.}$ $1 W_{\bullet}$ $W.M.$		
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	on corner		
<u> </u>				
New Well 🔼 Deepening 🗌 Reconditioning 🗍 Abandon 🗍				
If abandonment, describe material and procedure in Item 12.				
(3) TYPE OF WELL: (4) PROPOSED USE (check): Rotary	(12) WELL LOG: Diameter of well Depth drilled 892 ft. Depth of comp	~ 9nn		
Dug ☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐				
CASING INSTALLED: Threaded Welded 45. 6 "Diam from -0- ft to 81 ft Gage • 250	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.			
ft. to ft. Gage	MATERIAL	From To SWL		
ft. dage ft. Gage	Top soil - clay	0 7 .		
PERFORATIONS: Perforated? Yes No.	Boulders - broken rock	7 18		
Type of perforator used	Soft broken rock - gray	18 84		
	Hard gray rock, broken	84 102		
Size of perforations in. by in.	Soft gray & brown rock	102 127		
perforations from ft. to ft.	Hard gray rock	127 130		
perforations from ft. to ft.	Soft brown & gray rock	130 135		
perforations fromft. to ft.	Red rock	135 152		
perforations from ft. to ft.	Soft brown & gray rock	152 192		
perforations from ft. to ft.	Black rock	192 201		
(7) SCREENS: Well screen installed? Yes M No	Green rock	201 211		
Manufacturer's Name	Black rock	211 246		
Type	Soft rock, blk to brn to red	246 287		
Diam. Slot size Set from ft. to ft.	Black rock	287 339		
Diam. Slot size Set from ft. to ft.	Broken black rock	339 351		
	Gray rock, broken	351 366		
(8) WATER LEVEL: Completed well.	Soft gray & brown rock	366 388		
Static level 520 ft. below land surface Date 11/8/68	Gray rock, broken	388 413		
sian pressure lbs. per square inch Date	Soft gray broken rock	413 430		
(0) THEFT THESING Drawdown is small with the land in	Brown rock	430 439		
(9) WELL TESTS: Drawdown is amount water level is lowered below static level	Brown & gray rock	439 515		
Was a pump test made? [] Yes No If yes, by whom?	Hard brown & gray rock	515 527		
Yield: gal./min. with ft. drawdown after hrs.	Work started 9/9/68 19 Complete	ted 3/29/69 ₁₉		
" " "	Date well drilling machine moved off of well	3/30/69 19		
" " " "	Drilling Machine Operator's Certification:			
AIRLIFT 30 gal./min. with 230ft. drawdown after 2 hrs.	This well was constructed under my drials used and information reported aboundingles and belief.	irect supervision. Mate- ve are true to my best		
Artesian flow g.p.m. Date	1. / //. n () .	a 6/02/60		
Temperature of water Was a chemical analysis made? ☐ Yes ☐ No	(Drilling Machine Operator)	Date 6/23/69 19		
(10) CONSTRUCTION:		235		
Well seal—Material used Cement	Drilling Machine Operator's License No.	······································		
Depth of seal 84 ft	Water Well Contractor's Certification:			
Diameter of well bore to bottom of seal10in.		iction and this report in		
Were any loose strata cemented off? Yes No Depth	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes XNo	NAME A. M. Jannsen Drilling	Co.		
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type or print)		
	Address 21075 S. W. Tualatin V			
Type of water? depth of strata	SA STILL	Oregon		
Method of sealing strata off	[Signed] Edward W L	undlin		
Was well gravel packed? Yes No Size of gravel:	(Water Well Contra			
Gravel placed from ft. to ft.	Contractor's License No. 79 Date	6/23/69 19		

Gravel placed from

NOTICE TO WATER WELL CONTRACTOR. The original and first popy of this report are to be filed with the STATE ENGINEER SALES.

WASH

State Permit No.

00916.3

filed with the STATE OF QREGON
STATE ENGINEER, SALEM, OREGON 97310

within 30 days from the date (Please type or print)
of well completion. of well completion. PAGE "2"

G-4248

(1) OWNER:	(11) LOCATION OF WELL:				
Name Cooper Mountain Water District	County Washington Driller's well number				
Address	14 14 Section 31 T. 1 S R. 1 W. W.M.				
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision	n corner			
New Well Deepening Reconditioning Abandon abandon abandon abandonment, describe material and procedure in Item 12.					
Potower C Dwiven C	(12) WELL LOG: Diameter of well below casing				
Cable	Depth drilled it. Depth of comp	leted wel	1	_ ft.	
Dug Bored Irrigation Test Well Other	Formation: Describe color, texture, grain size	and struc	cture of n	naterials;	
CASING INSTALLED:	and show thickness and nature of each strate with at least one entry for each change of form	nation. R	Report each	h change	
" Diam. from ft. to ft. Gage	in position of Static Water Level as drilling pr	oceeds. I	Note drilli	ng rates.	
" Diam. from ft. to ft. Gage		From	- To	SWL	
" Diam, from ft. to ft. Gage	Brown & gray rock	527	5111		
PERFORATIONS: Perforated? Yes No.	Weathered basalt 3 gpm	544	568	514	
Type of perforator used	Brown & gray rock	568	581		
Size of perforations in. by in.	Hd gray basalt-brn streaks	581	600		
perforations from ft. to ft.	Weathered basalt 10 gpm	600	61/4		
perforations from ft. to ft.	DIOMI & STAY TOOK	628	628 634		
perforations fromft. toft	TIGHT OF ONLY TO ATT	634	673		
perforations from ft. to ft.	I BUT DUE A LOCK WITHIN DETERMINE	673	708		
perforations from ft. to ft.	THE STATE OF THE S		1.00		
	soft layers	708	758		
(7) SCREENS: Well screen installed? ☐ Yes ☐ No	Brown & gray rock - hard	758	772		
Manufacturer's Name	" Hard brown & gray rock-soft	772	794		
Type Model No	Brown & gray rock	794	814		
Diam, Slot size Set from ft. to ft.	Broken gray rock, some brn.	874	845		
Diam. Slot size Set from ft. to ft.	Hard gray broken rock	845	892		
(8) WATER LEVEL: Completed well.			·		
Static level ft. below land surface Date		<u> </u>	 		
Sian pressure lbs. per square inch Date				 	
(9) WELL TESTS: Drawdown is amount water level is	- <u>"#/ </u>	 	 		
lowered below static level-			 	 	
Was a pump test made? Yes No If yes, by whom?	Work started 19 Comple	ted.	4	19	
Yield: gal./min. with ft. drawdown after hrs				19	
" " "	Bate wen drining ingenine moved out of wen				
n n n n	Drilling Machine Operator's Certification			35-4-	
Bailer test gal./min. with ft. drawdown after hrs	This well was constructed under my carrials used and information reported about	nrect su ove are	true to	my bes	
Artesian flow g.p.m. Date	knowledge and belief.				
Temperature of water Was a chemical analysis made? Yes N	[Signed]				
(10) CONSTRUCTION:	Drilling Machine Operator's License No				
Well seal—Material used					
Depth of seal f		31-41			
Diameter of well bore to bottom of seal in.	true to the best of my knowledge and bel	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Were any loose strata cemented off? Yes No Depth	•••				
Was a drive shoe used? ☐ Yes ☐ No	NAME (Person, firm or corporation)	(Ту	pe or print)	
Did any strata contain unusable water? Yes No	Address				
Type of water? depth of strata	-				
Method of sealing strata off	[Signed] (Water Well Contr				
Was well gravel packed? Yes No Size of gravel:	(Water Well Contr	acto r)			