SPARINGS	WASH	
NOTICE TO WATER WELL CONTRACTOR The original and first copy	- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	,
of this report are to be MAY 19 WATER WELL REPORT 09598 State Well No. /2w-6		
STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion. STATE OF OREGON State Permit No.		
(1) OWNER:	lowered below static level	
Name () Com (OSes Jun C	Was a pump test made? Yes \(\subseteq \text{No If yes, by whom?} \)	
Address // // Fag TV, HVV	1170/EagT TV, HWV Yield: 20 gal./min. with 16 ft. drawdown after 48 hrs.	
Hinshord Oregon """		
(2) LOCATION OF WELL:	" " " " "	
County Warh. Driller's well number	Bailer test gal./min. with ft. drawdov	vn after hrs.
1/4 Section L T. 18 R. 9 W.M.	Artesian flow g.p.m. Date	The state of the s
Bearing and distance from section or subdivision corner	Temperature of water 6 Was a chemical analysis m	ade? Yes No
Bearing and distance from section of subdivision corner	(12) WELL LOG: Diameter of well below ca	sing 3#
	Depth drilled 46 ft. Depth of completed we	11 43 4
The state of the s	Formation: Describe by color, character, size of material	
	show thickness of aquifiers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.	
	stratum penetratea, with at teast one entry for each change of formation.	
	MATERIAL	FROM TO
(3) TYPE OF WORK (check):	Good black rail	0 411
New Well ▶ Deepening ☐ Reconditioning ☐ Abandon ☐	Marin Olas	4 19.
andonment, describe material and procedure in Item 12.	Lises sand	13 10
(4) PROPOSED USE (check): (5) TYPE OF WELL:	Bunkle Assal teasill	18 91
Rotary □ Driven □	Hill was the Market of the Mar	26 28
Domestic Industrial Municipal Cable Jetted	The said of the sentences	28 32
Irrigation 💆 Test Well 🗌 Other 🔲 Dug 🗍 Bored 🟋	Flind prist. Hereland	29 34
(6) CASING INSTALLED: Threaded Welded W	The state of the s	711 01
	Alfan Carlotte	7 36 14
6 "Diam. from 0 ft. to 76 ft. Gage Two	gricy clay mayi	26 701
" Diam. from	pear passa	10 F34
" Diam. from ft. to ft. Gage		
(7) PERFORATIONS: Perforated? ☐ Yes X No		
Type of perforator used		47 42 4.3
Size of perforations in. by in.		, in
perforations from ft. to ft.		
perforations from		· · · · · · · · · · · · · · · · · · ·
perforations from ft, to ft.		V + 4.
perforations from		
perforations fromft. toft.		***
(8) SCREENS: Well screen installed? ☐ Yes ¥ No	•	
Manufacturer's Name		
Type Model No.		
Slot size Set from ft. to ft.	Work started WW 5 19 4 Completed M	1964
Diam Slot size Set from ft. to ft.	Date well drilling machine moved off of well May	19/4
(9) CONSTRUCTION:		20 1067
•	(13) PUMP:	
Well seal—Material used in seal Bentonita	Manufacturer's Name	PATANCAY WYAY HAAN MANAGANAAN ANGAN
Depth of sealft. Was a packer used?	Type:	P
Diameter of well bore to bottom of seal		
Were any loose strata cemented off? Yes No Depth	ere any loose strata cemented off? Yes No Depth	
Was a drive shoe used? Yes X No	This well was drilled under my jurisdiction a	nd this report is
Was well gravel packed? Yes No Size of gravel: true to the best of my knowledge and belief.		
Gravel placed fromft. toft. NAME \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \		
id any strate contain unusuable water? Ves M No		
Type of water? depth of strata Address 43189 Hullsford Chr		
Method of sealing strata off		
(10) WATER LEVELS: Drilling Machine Operator's License No.		
FCI-ma 37		
Static level 6 ft. below land surface Date	[Signed](Water Well Contractor)	TEXT
Artesian pressure lbs. per square inch Date	Contractor's License No. 17. D. Date May.	19/9
(USE ADDITIONAL SHEETS IF NECESSARY)		