WASH

REGEIVED

STATE OF OREGON
WATER WELL REPORT 009628
(as required by ORS 537.765)

6561 0 3 JAM

10626 10626

(as required by ORS 537.765)	(START CARD) #106		
(1) OWNER: Well Number: TW// NW Name Oregon Garden Products S	6 (9) POCATION OF WELL by legal d ALEM. OREGON Count Washington Latitude	escription:	·
Address 3150 S. E. Minter Bridge Rd.	Count Washington attitude	Longitude	
City Hillsboro State OR Zip 97123	Township 1 S N or S, Range 2 W	E or W	, WM.
(2) TYPE OF WORK:			
<u> </u>	Tax Lot Block		
New Well Deepen Recondition X Abandon emporar			
(3) DRILL METHOD	Bridge Rd., Hillshoro, Oregon 97123		
Rotary Air X Rotary Mud Cable	(10) STATIC WATER LEVEL:		
Other	ft. below land surface.		
(4) PROPOSED USE:	Artesian pressure lb. per square inch. Date		
☐ Domestic ☐ Community ☐ Industrial ☐ Irrigation	(11) WATER BEARING ZONES:		
☐ Thermal ☐ Injection ☐ Other <u>Test Well</u>			
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first found		
Special Construction approval Yes No Depth of Completed Well — ft.	From To Estir	nated Flow Rate	SWL
Explosives used Type Amount			
HOLE SEAL Amount			
Diameter From To Material From To sacks or pounds 10" 0 18 Gran. Bentn. 0 18 8 sacks			
10" 0 18 Gran. Bentn. 0 18 8 sacks 6½" 18 228 Drill gel	(12) WELL LOG: Crown claustics		<u> </u>
JO DE DE LE GOL	Ground elevation		
	Material	From To	SWL
How was seal placed: Method	Rock & clay fill	0 1	
Other poured into dry anulas	Gray clay	1 2	
Backfill placed fromft. toft. Material	Soft brown clay	2 8	
Gravel placed fromft. toft. Size of gravel	Soft brown silty clay	8 15	
	Fine brown muddy sand	15 38	
(6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Threaded	Soft gray silty clay	38 49	
(1) 11 10 0 0 0 0	Fine gray muddy sand	49 88	
	Sticky dark gray clay	88 96	
	Fine to med. black sand/some	96 110	
	wood & clay		
Liner:	Med. to coarse black sand	110 136	
	Sticky gray clay	136 141	· · · · · ·
Final location of shoe(s)	Soft brown sandy clay	141 148	
(7) PERFORATIONS/SCREENS:	Coarse brown & black sand	148 151	
	Sticky light gray clay	151 156	
Perforations Method	Soft light brown clay	156 158	
Screens Type Material	Coarse brown & black sand	158 164	
Slot Tele/pipe From To size Number Diameter size Casing Liner	Sticky gray-brown clay	164 178'	
size Rumber Blameter Size Casing Liner	Soft gray clay	178 183	
	Sticky light gray clay	183 196	
	Soft brown clay	196 207	
	Sticky gray clay	207 228	
	D		
	Date started 5/17/89 Completed	5/19/89	
(8) WELL TESTS: Minimum testing time is 1 hour	(unbonded) Water Well Constructor Certificati	on:	
Flowing	I certify that the work I performed on the con	nstruction, altera	tion, or
☐ Pump ☐ Bailer ☐ Air ☐ Artesian	abandonment of this well is in compliance with Oregon well construction standards. Materials used and information reported above are true to my best		
Yield gal/min Drawdown Drill stem at Time	knowledge and belief.		
1 hr.	W	WC Number	-
	Signed Da	ate	
	(bonded) Water Well Constructor Certification:		
Temperature of water Depth Artesian Flow Found	I accept responsibility for the construction, alteration, or abandonment		
Was a water analysis done? Yes By whom	work performed on this well during the construction dates reported above all		
work performed during this time is in compliance with Oregon well construction standards. This report is true to the best of my knowledge and			
Solter A Months To Otto To Ott			
Depth of strata: Date 5/25/89			
	Vapanus	ne 1/23/89	