

NOTICE TO WATER WELL CONTRACTOR
The original and first copy
of this report are to be
filed with the

WHEELER WATER WELL REPORT RECEIVED

STATE ENGINEER, SALEM, OREGON 97310
within 30 days from the date
of well completion.

STATE OF OREGON
(Please type or print)

APR 7 1975

State Well No. 85/22E-106A

STATE ENGINEER
SALEM, OREGON

State Permit No.

(1) OWNER:

Name State Highway Div. Parks (Shelton)
Address Salem, Oregon

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary Driven
Cable Jetted
Dug Bored

(4) PROPOSED USE (check):

Domestic Industrial Municipal
Irrigation Test Well Other

CASING INSTALLED:

Threaded Welded
6" Diam. from + 1 1/2 ft. to 58 1/2 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:

Perforated? Yes No.

type of perforator used machine
Size of perforations 1/8 in. by 3 in.
240 perforations from 18 1/2 ft. to 58 1/2 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? Yes No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom driller
Yield: 14 gal./min. with 3 ft. drawdown after 1/2 hrs.
19 " 4 " 1/2 "
26 " 5 " 1 1/2 "
Baller test gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.

Temperature of water 50 Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used cement
Well sealed from land surface to 19 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 9 sacks
Number of sacks of bentonite used in well seal 0 sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons
of water lbs./100 gals.
Was a drive shoe used? Yes No Plugs Size: location ft.
Did any strata contain unusable water? Yes No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? Yes No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Wheeler Driller's well number
NE 1/4 NW 1/4 Section 10 T. 8S R. 22 E W.M.
Bearing and distance from section or subdivision corner
1668' East + 320' South of NW
corner Sec. 10

(11) WATER LEVEL: Completed well.

Depth at which water was first found ft.
Static level 18 ft. below land surface. Date 3/31/75
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 8
Depth drilled 62 ft. Depth of completed well 60 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
heavy brown soil	0	2	
boulders @ congl	2	5	
brownish-gray sandstone	5	23	
br-clay soft gray shale (water)	23	60	
med. hd. br. rock (60	62	18'

Work started 3/26 19 75 Completed 3/31 19 75
Date well drilling machine moved off of well 3/31 19 75

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Dale Paul Dew Date 3/31, 19 75
(Drilling Machine Operator)

Drilling Machine Operator's License No. 934

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Crawford Well Drilling
(Firm or corporation) (Type or print)

Address 3626 Coyner Redmond, Ore, 97756

[Signed] John V. Johnson
(Water Well Contractor)

Contractor's License No. 595 Date 3/31, 19 75