NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED
OCT 27 1975
WATER RESOURCES DEPT.
SALEM, OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

WHEE 124

State Well No. 8S/23E .13

State Permit No.

(1) OWNER:
Name ART Robison
Address Fossil, OREGON

(2) TYPE OF WORK (check):
New Well ☐ Deepening ☒ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☐ Industrial ☐ Municipal ☐
Irrigation ☒ Test Well ☐ Other ☐

(5) CASING INSTALLED:
Threaded ☐ Welded ☒
10" Diam. from +2 ft. to ? ft. Gage 312
8" Diam. from +2 ft. to 100 ft. Gage 188
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:
Perforated? ☒ Yes ☐ No.
Type of perforator used SAW
Size of perforations ⅛ in. by 3" in.
680 perforations from 30 ft. to 100 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 75 gal./min. with 12 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water 59 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used undetermined
Well sealed from land surface to ft.
Diameter of well bore to bottom of seal in.
Diameter of well bore below seal in.
Number of sacks of cement used in well seal sacks
Number of sacks of bentonite used in well seal sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☒ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Wheeler Driller's well number ART #1
SW ¼ SW ¼ Section 13 T. 8S R. 23E W.M.
Bearing and distance from section or subdivision corner
212 N & 375 E of SW corner Sec 13

(11) WATER LEVEL: Completed well.
Depth at which water was first found unknown ft.
Static level ~~+8~~ 8 ft. below land surface. Date 9 Sept 75
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 8"
Depth drilled 102 ft. Depth of completed well 100 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
grey clay & fine black gravel	50	55	10
grey clay stone & Med. Sand	55	102	8

Work started 4 Sept 1975 Completed 9 Sept 1975
Date well drilling machine moved off of well 10 Sept. 1975

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Tom Landwer (Drilling Machine Operator) Date 9 Sept., 1975
Drilling Machine Operator's License No. 840

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name BLUE MT. WELL DRILLING (Person, firm or corporation) (Type or print)
Address P.O. 117 SPRAY, OREGON
[Signed] Tom Landwer (Water Well Contractor)
Contractor's License No. 598 Date 9 Sept, 1975

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119