

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON (Please type or print)

(Do not write above this line)

RECEIVED

MAR 28 1977

State Well No. 2s/3w-3ku G-7785 #1

WATER RESOURCES DEPT. SALEM, OREGON

(1) OWNER:

Name Dr. Melvin M. Reeves, M. D. Address Yamhill, Oregon

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

CASING INSTALLED:

6" Diam. from 0 ft. to 40 ft. Gage .25 Threaded [] Welded [X] 4" Diam. from 40 ft. to 180 ft. Gage PVC

PERFORATIONS:

Perforated? [X] Yes [] No.

Type of perforator used Drill Size of perforations 1/2 Inch Circular 135 perforations from 120 ft. to 180 ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name Type Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No If yes, by whom? Yield: gal./min. with ft. drawdown after hrs. Compressor Bailer test 12 gal./min. with 140 ft. drawdown after 1 1/2 hrs.

(9) CONSTRUCTION:

Well seal—Material used Cement Grout Well sealed from land surface to 40 ft. Diameter of well bore to bottom of seal 9 in. Diameter of well bore below seal 6 in. Number of sacks of cement used in well seal 4 1/2 sacks Number of sacks of bentonite used in well seal 0 sacks Brand name of bentonite Number of pounds of bentonite per 100 gallons of water lbs./100 gals. Was a drive shoe used? [] Yes [X] No Plugs Size: location ft. Did any strata contain unusable water? [] Yes [X] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [] Yes [X] No Size of gravel: Gravel placed from ft. to ft.

(10) LOCATION OF WELL:

County Yamhill Driller's well number NE 1/4 SW 1/4 Section 31 T. 2S R. 3W W.M. Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 71 Ft. 5gpm ft. Static level 34 ft. below land surface. Date Mar. 24 Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0 Depth drilled 180 ft. Depth of completed well 180 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

Table with 4 columns: MATERIAL, From, To, SWL. Rows include Topsoil, Red & Brown Clays, Brown & Red Decomposed clay, Firm Gray Shale w/ unstable layers, Firm Gray Siltstone.

Work started Mar. 23 1977 Completed Mar. 24 1977 Date well drilling machine moved off of well Mar. 24 1977

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] James H. Wilcox Date Mar. 24, 1977. (Drilling Machine Operator)

Drilling Machine Operator's License No. 172

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Wilcox Drilling & Pump Co. (Person, firm or corporation) (Type or print)

Address P. O. Box 569, McMinnville, Oregon 97128

[Signed] James H. Wilcox (Water Well Contractor)

Contractor's License No. 428 Date Mar. 24, 1977