NOTICE TO WATER WELL CONTINUE C LATER WELL REPORT of this report are to be filed with the JUL 18 1968 STATE OF OREGON STATE ENGINEER, SALEM, OREGON AT E ENGINEER type or print) within 30 days from the date A I E ENGINEER write above this line) of well completion. SALEM. OREGON

YAMH 1/35

State Well No.	2/3	3W-	31	N
----------------	-----	-----	----	---

State	Well No	<u>الم</u>	36	, and the second	<u>3/</u>	_/ <u>/</u>
State	Permit No					

(1) OWNER:	(11) LOCATION OF WELL: Yamhill Priller's well number				
Name Henry Thompson Address Rte. 2 Box 56A, Yamhill, Oregon	County Diller's well number				
Address Rte. 2 Box Joh; -gmillit, 01 080-	5W 14 5W 14 Section 3/ T. 25 R. 3W W.M.				
(2) TYPE OF WORK (check):	Bearing and distance from section or subdivision corner				
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐					
If abandonment, describe material and procedure in Item 12.					
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(12) WELL LOG: Diameter of well below casing 6 In.				
Rotary Driven Domestic Mindustrial Municipal	Diameter of weir below cusing				
Cable	Depth diffed 17/7 21. Depth of output				
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,				
CASING INSTALLED: Threaded Welded	with at least one entry for each change of formation. Report each change				
" Diam. from ft. to ft. Gage • 250	in position of Static Water Level as drilling proceeds. Note drilling rates.				
" Diam. from ft. to ft. Gage	MATERIAL From To SWL				
	Topsoil 0 2 Brown & Red Clays 2 27				
PERFORATIONS: Perforated? Yes Yes No.	Brown & Red Clays 2 27 Firm Gray Siltstone 27 106				
Type of perforator used	Firm Yellow Sandstone 196 113				
Size of perforations in. by in.	Firm Gray silstone 113 153				
perforations from ft. to ft.					
perforations from ft. to ft.					
perforations from ft. to ft.					
perforations from ft. to ft.					
perforations from ft. to ft.					
(7) SCREENS: Well screen installed? Yes I No					
Manufacturer's Name					
Type Model No					
Diam. Slot size Set from ft. to ft.					
Diam Slot size Set from ft. to ft.					
(8) WATER LEVEL: Completed well.					
Static level 42 ft. below land surface Date 7-10-68					
ian pressure lbs. per square inch Date					
(9) WELL TESTS: Drawdown is amount water level is lowered below static level					
Was a pump test made? ☐ Yes 🔼 No If yes, by whom?	Work started July 3 1968 Completed July 10 1968				
Yield: gal./min. with ft. drawdown after hrs.	Date well drilling machine moved off of wellJuly 10 1968				
" " "	Drilling Machine Operator's Certification:				
108	This well was constructed under my direct supervision. Mate-				
	rials used and information reported above are true to my best knowledge and belief.				
Artesian flow g.p.m. Date	100000 11/1/1/1/1/ TUTY 77 068				
Temperature of water 50 Was a chemical analysis made? Yes No	[Signed] Willing Machine Operator)				
(10) CONSTRUCTION: Well seal—Material used Cement Grout & Drill Cut	Drilling Machine Operator's License No. 172				
	Water Well Contractor's Certification:				
Depth of seal 24 ft.	This well was drilled under my jurisdiction and this report is				
Diameter of well bore to bottom of seal	true to the best of my knowledge and belief.				
Was a drive shoe used? Yes No	NAME Wilcox Drilling & Pump Co.				
Did any strata contain unusable water? Yes 1 No No	(Person, firm or corporation) (Type or print) Oregon				
Type of water? depth of strata	Address				
Method of sealing strata off	round James H. Il Le Vian				
Was well gravel packed? ☐ Yes ☐ No Size of gravel:	[Signed] (Water Well Contractor)				
Gravel placed from ft. to ft.	Contractor's License No. 428 Date July 11 , 1968				
WENT TO PROVIDE ALVALE PROPERTY OF THE TOTAL TOT	· · · · · · · · · · · · · · · · · · ·				