3
STATE OF OREGON
WATER WELL REPORTER RESOURCES DEATE
(as required by ORS 537.765) SALEM, OREGON

| 1 | Yamh (121) | c |
|---|------------|----|
| _ | START | C. |

| | 35/36 | 126 ab |
|---|-------|--------|
| _ | 16254 | |

| (1) OWNER: Well Number: 1177 | (9) LOCATION OF WELL by legal description: |
|---|---|
| Name FRANK STILLER | County YAMHILL Latitude Longitude Township 3 S Nor S, Range 3 W E or W, WM. Section 26 NW 4 NE 4 |
| Address 21800 NE COVE ORCHARD RD | Township 3 S Nor S. Range 5 W E or W, WM. |
| City YAMHILL State OR Zip 97148 | Section 20 NW 4 NE 4 |
| (2) TYPE OF WORK: | Tax Lot Block Subdivision |
| New Well Deepen Recondition Abandon | Street Address of Well (or nearest address) VIEWMONT D AT ALDER DR. DUNDEE, |
| (3) DRILL METHOD | |
| Rotary Air Rotary Mud Cable | (10) STATIC WATER LEVEL: |
| Other | 150 .ft. below land surface. Date 09/28/90 |
| (4) PROPOSED USE: | Artesian pressure lb. per square inch. Date |
| Domestic Community Industrial Irrigation | (11) WATER BEARING ZONES: |
| Thermal | Depth at which water was first found 219 |
| (5) BORE HOLE CONSTRUCTION: 248 | THE LINE DAY CANA |
| Special Construction approval Yes No Depth of Completed Well t. | From To Estimated Flow Rate SWL |
| Yes No L L Amount Amount | 219 224 16 150 |
| | 240 243 2.5 150 |
| HOLE SEAL Amount Diameter From To Material From To sacks or pounds | |
| 10 0 79 CEMENT 0 79 21 SAX | (12) WELL LOG: Ground elevation |
| 6 79 248 | Gloding circuiton |
| | Material From To SWL |
| | RED TOP SOIL 0 4 |
| How was seal placed: Method | DENSE RED CLAY 4 20 |
| Otherft. toft. Material | SOFT BROWN CLAY 20 68 |
| Gravel placed fromft. toftSize of gravel | GRAY/GREEN MARINE SEDIMNT68 70 |
| | GRAY BASALT 70 219 |
| (6) CASING/LINER: Diameter From To Gauge Steel Plastic Welded Threaded | |
| Casing: $6 + 1 79 .25 \square X \square \square X$ | GRAY BASALT 224 231 |
| | DECAYED BASALT 231 232 |
| | GRAY BASALT 232 240 |
| | DECAYED BASALT 240 243 150 GRAY BASALT 243 248 |
| Liner: 4 0 248 160# \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ | GRAY BASALT 243 248 |
| | |
| Final location of shoe(s) | |
| (7) PERFORATIONS/SCREENS: SAW | |
| Perforations Method | |
| m t i t | |
| From To size Number Diameter size Casing Liner | BLUE WATER DRILLING CO. |
| 208 248 6" 64 | DAYTON, OR. 97114 |
| | |
| | |
| | Date started 09/26/90 Completed 09/27/90 |
| | Date started |
| (8) WELL TESTS: Minimum testing time is 1 hour | (unbonded) Water Well Constructor Certification: I certify that the work I performed on the construction, alteration, or |
| Flowing | abandonment of this well is in compliance with Oregon well construction |
| | standards. Materials used and information reported above are true to my be knowledge and belief / 1438 |
| Yield gal/min Drawdown Drill stem at Time | WWC Number |
| 18.50 248 1 hr. | - Signed Date 09/28/90 |
| | (bonded) Water Well Constructor Certification: |
| | I accept responsibility for the construction, alteration, or abandonment |
| Temperature of water Depth Artesian Flow Found | work performed on this well during the construction dates reported above. a work performed during this time is in compliance with Oregon we |
| Was a water analysis done? Yes By whom | construction standards. This report is true to the best of my knowledge ar |
| ☐ Salty ☐ Muddy ☐ Odor ☐ Colored ☐ Other | |
| Depth of strate: | Signed Molosel & helberse Date 4-30-40 |