

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

YAMH

WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this line)

RECEIVED DEC 13 1968 STATE ENGINEER SALEM OREGON

State Well No. 2S/4W-22d

STATE ENGINEER

(1) OWNER:

SALEM OREGON

Name Larry Harrington Address Rt. 2 Box 430 Gaston, Oregon

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [x] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

Threaded [] Welded [x]

6" Diam. from 0 ft. to 200 ft. Gage .25

(6) PERFORATIONS:

Perforated? [x] Yes [] No.

Type of perforator used Torch Size of perforations 3/16 in. by 12 in. 170 perforations from 30 ft. to 200 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No

Manufacturer's Name Type Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 70 ft. below land surface Date Aug. 11, 67 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [x] No If yes, by whom? Yield gal./min. with ft. drawdown after hrs. Bailer test 10 gal./min. with 20 ft. drawdown after 2 hrs. Artesian flow g.p.m. Date Temperature of water 58 Was a chemical analysis made? [] Yes [x] No

(10) CONSTRUCTION:

Well seal—Material used Grout and Bentonite Depth of seal 30 ft. Diameter of well bore to bottom of seal 10 in. Were any loose strata cemented off? [] Yes [x] No Depth Was a drive shoe used? [] Yes [x] No Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [x] Yes [] No Size of gravel 3/8-3/4 Gravel placed from 30 ft. to 200 ft.

(11) LOCATION OF WELL:

County Yamhill Driller's well number 1/4 S. E. 1/4 Section 22 T. 2 S. R. 4 W. W.M. Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing

Depth drilled 206 ft. Depth of completed well 200 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows: Surface Soil (0-2), Yellow & Brown Clay (2-30), Blue Shale (30-200)

Work started 8/4 1967 Completed 8/11 1967

Date well drilling machine moved off of well 8/11/67 19

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Glenn Mosher Date 8-11, 1967 (Drilling Machine Operator)

Drilling Machine Operator's License No. 537

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Mosher Drilling Co. (Person, firm or corporation) (Type or print)

Address McMinnville, Oregon

[Signed] Ed Mosher (Water Well Contractor)

Contractor's License No. 430 Date 8-11, 1967