

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON, within 30 days from the date of well completion

RECEIVED MAY 20 1969 STATE ENGINEER SALEM OREGON

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

Do not write above this line

YAMH

1615

State Well No. 2/SW-3166

State Permit No.

(1) OWNER:

Name Bryce Mitchell
Address Rte. 1 Box 95C, Yamhill, Oregon

(2) TYPE OF WORK (check):

New Well [X] Deepening [] Reconditioning [] Abandon []

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [X] Cable [] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [X] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

6" Diam. from 0 ft. to 20 ft. Gage .250
Threaded [] Welded [X]

PERFORATIONS:

Perforated? [] Yes [X] No

Type of perforator used

Size of perforations in. by in.
perforations from ft. to ft.

(7) SCREENS:

Well screen installed? [] Yes [X] No

Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 21 ft. below land surface Date 5-13-69

Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a pump test made? [] Yes [X] No If yes, by whom?

Flow: gal./min. with ft. drawdown after hrs.

Bailer test 25 gal./min. with 50 ft. drawdown after 1 hrs.

Artesian flow g.p.m. Date

Temperature of water 44 Was a chemical analysis made? [] Yes [X] No

(10) CONSTRUCTION:

Well seal—Material used Cement Grout & Drill cuttings

Depth of seal 19 ft.

Diameter of well bore to bottom of seal 8 in.

Were any loose strata cemented off? [] Yes [X] No Depth

Was a drive shoe used? [] Yes [X] No

Did any strata contain unusable water? [] Yes [X] No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? [] Yes [X] No Size of gravel:

Gravel placed from ft. to ft.

(11) LOCATION OF WELL:

County Yamhill Driller's well number
NW 1/4 NW 1/4 Section 31 T. 25 R. 5W W.M.
Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 6 In.

Depth drilled 91 ft. Depth of completed well 90 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with 4 columns: MATERIAL, From, To, SWL. Rows include Topsoil, Red & Yellow Clays, with boulders, Hard gray & blue siltstone with layers of gray limestone.

Work started May 9 19 69 Completed May 13 19 69

Date well drilling machine moved off of well May 13 19 69

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] James H. Wilcox May 18, 19.69 (Drilling Machine Operator)

Drilling Machine Operator's License No. 172

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME Wilcox Drilling & Pump Co. (Person, firm or corporation) (Type or print)

Address P. O. Box 569, McMinnville, Oregon

[Signed] James H. Wilcox (Water Well Contractor)

Contractor's License No. 428 Date May 18, 1969