## NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion. WATER WELL REPORT (Please type or print) (Do not write above this line)

YAM H State Well No. 25/6ω-ca

1637 State Permit No.

SP\*45656-119

WATER RESOURCES DEPT	
(1) OWNER: SALEM, OREGON	(10) LOCATION OF WELL:
Name BRICE SITCHELL	County MANIEL Driller's well number
Address RT / Box 95C	SW 1/2 NF 1/4 Section 25 T. 25 R. 6W W.M.
YAMHILL, ORE.	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (check):	Dearing and amounted from position of
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	CALL THE PROPERTY OF TAXABLE PARTY.
	(11) WATER LEVEL: Completed well.
(3) TYPE OF WELL: (4) PROPOSED USE (check):  Proposed For Public USE	Depth at which water was first found 50 ft.
Rotary   Driven   Domestic   Industrial   Municipal	Static level 27 ft. below land surface. Date 1/15/5
Dug	Artesian pressure lbs. per square inch. Date
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing
6" Diam. from # 215 ft. to 36 ft. Gage 1250	Depth drilled SO ft. Depth of completed well SO ft.
" Diam. from	Formation: Describe color, texture, grain size and structure of materials;
"Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated,
PERFORATIONS: Perforated? Y Yes No.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
	MATERIAL From To SWL
Type of perforator used	MATERIAL From 10 SW2
Size of perforations /4 in. by 12 in.	Top Sort
	BROKEN ROCK + BOULDERS 1 12
perforations from ft. to ft.	SHOLE, LOOSE 12 18
perforations from ft. to ft.	SHALE BLUE HARD 18 50
(7) SCREENS: Well screen installed? ☐ Yes Ø No	SHALE BLUE FRACTURED 50 80 27
(7) SCREENS: Well screen installed?  Wes No Manufacturer's Name	
Type Model No	A Section of the sect
Diam. Slot size Set from ft. to ft.	
Diam. Slot size Set from ft. to ft.	
Diam. Stot size Set from 16.	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	
Was a pump test made? ☐ Yes 💢 No If yes, by whom?	
Yield: gal./min. with ft. drawdown after hrs.	The second of th
" " "	
" " "	म्बर्ग के प्राप्त अवस्थित क्यों है। स्वर्ग के प्राप्त अवस्थित क्यों है।
Bailer test 50 gal./min. with 23 ft. drawdown after 2 hrs.	60 5 7 9
Artesian flow g.p.m.	
perature of water Depth artesian flow encountered ft.	Work started /// 19 75 Completed ///5 19 75
	Date well drilling machine moved off of well
(9) CONSTRUCTION:	
Well seal-Material used CEMENT	Drilling Machine Operator's Certification:  This well was constructed under my direct supervision.
Well sealed from land surface to	Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and benef.
Diameter of well bore below seal	[Signed] / War Sellaton (Brilling Machine Operator)
Number of sacks of cement used in well sealsacks	Drilling Machine Operator's License No
Number of sacks of bentonite used in well seal sacks	Drining Machine Operator's Interise 110.
Brand name of bentonite	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisdiction and this report is
of waterlbs./100 gals.	true to the best of my knowledge and belief.
Was a drive shoe used? X Yes 🗆 No Plugs Size: location ft.	Name MOSTHWEST WATER WELL DRILLINS
Did any strata contain unusable water?   Yes No	(Person, firm or corporation) (Type of print)
Type of water? depth of strata	Address 1851/14/ADAMS MAINNUILE, OSE
Method of sealing strata off	ssimual Which a Lordan
Was well gravel packed? ★ Yes □ No Size of gravel: FA	[Signed] (Water Well Contractor)
Gravel placed from 30 ft. to 80 ft.	Contractor's License No. 596. Date