\mathcal{W}

STATE OF OREGON

YAMH 1860

PAGE

SEP - 8 1992

9809C 10/91

WATER WELL REPORT (as required by ORS 537.765)

VIATER RESOURCES (START CARD) #_
SALEM. OPECON

(1) OWNER: Well Number /327	(9) LOCATION OF WELL by legal descrip	ption:		
Name CITY OF DAYTON, OREGON	County YAMHTILatitude L			
Address CITY HALL, FERRY ST.	Township 4 S N or S. Range 3 I	W	_E or W	. WM.
City DAYTON State OR Zip 97114	Section17NW¼ _SE_	1/4		_
(2) TYPE OF WORK:	Tax LotBlock	Subdivi	ision	·
New Well Deepen Recondition Abandon	Street Address of Well (or nearest address)			
(3) DRILL METHOD:	FLOWER AT ASH ST DAYTO			
☐ Rotary Air ☐ Rotary Mud ☐ ¥Cable	(10) STATIC WATER LEVEL:			
	ft. below land surface.	Date	-	-
(4) PROPOSED USE: Gravel Feeder Tube	Artesian pressure Ib. per square inch.			
Domestic Community Industrial Irrigation	(11) WATER BEARING ZONES:			
☐ Thermal ☐ Injection ☐ OTHER	(II) WILLIAM BEING ESTEES.			
(5) BORE HOLE CONSTRUCTION:	Depth at which water was first found			
Special Construction approval Yes No Depth of Completed Well 1018	Deput at which water was first found			
	From To Estima	ated Flow	Rate	SWL
Explosives used Yes No TypeX Amount X				
HOLE SEAL Amount			-	
Diameter From To Material From To sacks or pounds				
10 0 25 DENTION THE 25 25 25 25				
10 0 25 BENTONITEO 25 25 SAX				<u></u>
6 25 155	(12) WELL LOG:			
	Ground elevation			
How was seal placed: Method A B C D E Other Backfill placed from fit. to Material Gravel placed from FT AMPED ft. Size of gravel		г_ г		1
Other	Material	From	To	SWL
Backfill placed from ft. to to Material	TOP SOIL		4	
Gravel placed from ft. to ft. Size of gravel	FIRM BROWN CLAY	4	20	
(6) CASING/LINER:	BLUE CLAY	20	63	
(6) CASING/LINER: 106 To 155 Diameter From To 16auge Steel Plastic Welder Threaded	BLUE CLAY W/COARSE SAND	63	80	
Casing	GREEN CLAY	80	95	
	BLUE CLAY W/MED. SAND	95	105	
6 +1 108 .25 X \ \ \ \ \	BLUE CLAY W/MED. SAND &			<u></u>
	FINE GRAVEL	105	120	
Liner:	BLUE CLAY W/SOME SAND			t .
	BLUE CLAY W/COARSE SAND			
Final location of shoe(s)	MEDIUM GRAVEL			
(7) DEDEOD ATIONS (CODEENS.			-33-3	
Perforations Method	CASING INSTALLATION ONLY			
Screens Type Material	FOR PURPOSES OF INSTALL-	t I		
Slot Tele/pipe	ING PEA GRAVEL NEXT TO			
From To size Number Diameter size Casing Liner	SCREENED INTERVAL OF			
	EXISTING WATER WELL.			
	blue water drilling co.			
	dayton, or. 97114			
	uaycon, or . 97114			
				
	-			
(8) WELL TESTS: Minimum testing time is 1 hour	00/01/05			Д
Flowing	Date started 09/01/92 Completed _	09/0	1/92	<u> </u>
☐ Pump ☐ Bailer ☐ Air ☐ Artesian	(unbonded) Water Well Constructor Certification:			
Yield gal/min Drawdown Drill stem at Time	I certify that the work I performed on the construction ment of this well is in compliance with Oregon well const			
	used and information reported above are true to my best			
1 hr.			_	
	1 / CV (I faul.	WWC No	_	
	Signed Milk Charles	Date 09	<u>/02/</u>	<u> 192</u>
	(bonded) Water Well Constructor Certification:			
Temperature of Water Depth Artesian Flow Found	I accept responsibility for the construction, alteration			
Was a water analysis done? Yes By whom	formed on this well during the construction dates reported			
Did any strata contain water not suitable for intended use? Too little	during this time is in compliance with Oregon well construis true to the best of my knowledge and belief.	action stan	iuaras. I	ins repor
☐ Salty ☐ Muddy ☐ Odor ☐ Colored ☐ Other	No de to State Sta	WWC N	Number_	
Depth of strata:	Signed No or helburn	Date		
	ND COPY - CONSTRUCTOR THIRD COPY - CU	STOMER	R. 9	809C 10/9