NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

yamh 2001

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED AUG 8 1978 WATER RESOURCES DEPT. SALEM, OREGON

NC

State Well No. 3s/2w-3 6c

State Permit No.

(1) OWNER:
Name Hugh Weber
Address Rt 3 Box 122 A-1 Sherwood, Oregon 97140

(2) TYPE OF WORK (check):
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☑ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☑ Industrial ☐ Municipal ☐
Irrigation ☑ Test Well ☐ Other ☐

(5) CASING INSTALLED:
Threaded ☐ Welded ☑
6" Diam. from 0 ft. to 83 ft. Gage 250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS:
Perforated? ☐ Yes ☑ No.
Type of perforator used
Size of perforations in. by in.
perforations from ft. to ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS:
Well screen installed? ☐ Yes ☐ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:
Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☑ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 30 gal./min. with ft. drawdown after hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement
Well sealed from land surface to 83 ft.
Diameter of well bore to bottom of seal 10" 8" in.
Diameter of well bore below seal 6 in.
Number of sacks of cement used in well seal 23 sacks
How was cement grout placed? poured
Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☐ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☐ Yes ☑ No Size of gravel:
Gravel placed from ft. to ft.

(10) LOCATION OF WELL:
County Yamhill Driller's well number 14
NW ¼ SE ¼ Section 3 T. 3S R. 2W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 210 ft.
Static level 71 ft. below land surface. Date July 28-78
Artesian pressure lbs. per square inch. Date

(12) WELL LOG:
Diameter of well below casing 6"
Depth drilled ft. Depth of completed well ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
top soil Brown	1	2	
Clay Red	2	35	
clay Brown soft rock	35	65	
Basalt hard	65	83	
(20 gal water sealed off)	83	154	Basalt
Basalt softer Broken Brown	154	174	
Basalt hard Grey	174	210	
weathered basalt Red	210	215	71
weathered Basalt Bright Red	215	220	
Basalt Grey	220	300	

Work started July 27 1978 Completed July 29 1978
Date well drilling machine moved off of well July 29 1978

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Dale Adams Lyle Adams Date July 29, 1978
(Drilling Machine Operator)
Drilling Machine Operator's License No. 1292

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Lyle Adams
(Person, firm or corporation) (Type or print)
Address Rt 3 Box 122X 97123
[Signed] Lyle R. Adams
(Water Well Contractor)
Contractor's License No. 690 Date July 27, 1978

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119