NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

Yamh 2365

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED NOV 6 1974 STATE ENGINEER SALEM, OREGON

State Well No. 3S/2W-15
State Permit No.

(1) OWNER:
Name Rudolph Schaad
Address Rt 4, Box 341
Newberg, Ore 97132

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED: Threaded ☐ Welded ☒
6 5/8 OD" Diam. from 0 ft. to 140 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used cutting torch
Size of perforations 1/4 in. by 14 in.
30 perforations from 60 ft. to 139 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 18 gal./min. with at bottom ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used cement
Well sealed from land surface to 46 ft.
Diameter of well bore to bottom of seal 10 in.
Diameter of well bore below seal 8 in.
Number of sacks of cement used in well seal 4 sacks
Number of sacks of bentonite used in well seal 0 sacks
Brand name of bentonite
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☒ Yes ☐ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☒ Yes ☐ No Size of gravel: 3/8
Gravel placed from 46 ft. to 140 ft.

(10) LOCATION OF WELL:
County Yamhill Driller's well number
¼ ¼ Section 15 T.3S R. 2W W.M.
Bearing and distance from section or subdivision corner C-A-A

(11) WATER LEVEL: Completed well.
Depth at which water was first found 90 ft.
Static level 55 ft. below land surface. Date 10-12-74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 145 ft. Depth of completed well 145 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
top soil	0	4	
brown clay	4	23	
soft red rock	23	32	
soft gray rock	23	73	
soft brown rock	73	81	
med hard brown rock	81	92	
med hard gray rock	92	122	
brown basalt with some hard	122	145	55 ft
layers with small soft broken layers			

Work started 10-8 19 74 Completed 10-12 19 74
Date well drilling machine moved off of well 10-12 19 74

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] John H. Meeker (Drilling Machine Operator) Date 10-15, 19 74
Drilling Machine Operator's License No. 50

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name JOHN MEEKER WELL DRILLING (Person, firm or corporation) (Type or print)
Address 2902 Hoover Blvd., Newberg, Ore 97132
[Signed] John H. Meeker (Water Well Contractor)
Contractor's License No. 111 Date 10-15, 19 74

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119