NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

RECEIVED APR 12 1974 STATE ENGINEER SALEM OREGON

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

Yamh 2645

State Well No. 3S/2W-28
State Permit No.

(1) OWNER:
Name Walter C Gaibler
Address Rt 2 Box 152
Newberg, Ore 97132

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☐ Driven ☐
Cable ☒ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
6 5/8 OD" Diam. from 0 ft. to 74-4 ft. Gage .250
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

(6) PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used cutting torch
Size of perforations 17 in. by 1/4 in.
20 perforations from 20 ft. to 74 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☒ Yes ☐ No If yes, by whom? Meeker
Yield: 14 gal./min. with 30 ft. drawdown after 2 hrs.
" " " "
" " " "
Bailer test 15 gal./min. with 30 ft. drawdown after 1 hrs.
Artesian flow g.p.m.
Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used cement & bentonite
Well sealed from land surface to ~~Ex~~ 20 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 12 in.
Number of sacks of cement used in well seal 3 sacks
Number of sacks of bentonite used in well seal 1 sacks
Brand name of bentonite National
Number of pounds of bentonite per 100 gallons of water lbs./100 gals.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☒ Yes ☐ No Size of gravel: 3/8
Gravel placed from 20 ft. to 74 ft.

(10) LOCATION OF WELL:
County Yamhill Driller's well number
¼ ¼ Section 28 T. 3S R. 2W W.M.
Bearing and distance from section or subdivision corner C-B-A

(11) WATER LEVEL: Completed well.
Depth at which water was first found 20 ft.
Static level 4 ft. below land surface. Date 3-11-74
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6"
Depth drilled 74 ft. Depth of completed well ~~8~~ 74 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
top soil	0	5	
brown clay silt	5	26	
blue clay silt	26	52	
blue clay	52	56	
blue sand silt	62	65	
brown sand silt	65	72	
brown clay	72	74	4ft

Work started Mar 8 1974 Completed 3-11-74 19
Date well drilling machine moved off of well 3-11-74 19

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Robert R. Bletsch (Drilling Machine Operator) Date 3-11, 1974
Drilling Machine Operator's License No. 767

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name JOHN MEEKER WELL DRILLING (Person, firm or corporation) (Type or print)
Address 2902 Hoover Blvd, Newberg, Ore 97132
[Signed] John H Meeker (Water Well Contractor)
Contractor's License No. 111 Date 3-11, 1974

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119