

16

STATE OF OREGON WATER WELL REPORT (as required by ORS 537.765) WATER RESOURCES DEPT. SALEM, OREGON

MAR - 3 1994

Yamhill 3050 (START CARD) # 55/6W/29da 61364

(1) OWNER: Well Number \_\_\_\_\_ Name Delphian School Address 20950 Rock Cr. Rd. City Sheridan State OR Zip \_\_\_\_\_

(2) TYPE OF WORK: [X] New Well [ ] Deepen [ ] Recondition [ ] Abandon

(3) DRILL METHOD: [X] Rotary Air [ ] Rotary Mud [ ] Cable [ ] Other \_\_\_\_\_

(4) PROPOSED USE: [X] Domestic [ ] Community [ ] Industrial [ ] Irrigation [ ] Thermal [ ] Injection [ ] Other \_\_\_\_\_

(5) BORE HOLE CONSTRUCTION: Special Construction approval [ ] Yes [X] No Depth of Completed Well 260 ft. Explosives used [ ] Yes [X] No Type \_\_\_\_\_ Amount \_\_\_\_\_

Table with columns: HOLE Diameter, From, To, SEAL Material, From, To, Amount sacks or pounds. Rows include 10" 0 18 Bentonite 0 18 8 Sacks, 6" 18 60, 10" 60 65 Cement 60 65 4 Sacks, 6" 65 260.

How was seal placed: Method [ ] A [ ] B [X] C [ ] D [ ] E [ ] Other \_\_\_\_\_ Backfill placed from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Material \_\_\_\_\_ Gravel placed from \_\_\_\_\_ ft. to \_\_\_\_\_ ft. Size of gravel \_\_\_\_\_

(6) CASING/LINER: Table with columns: Diameter, From, To, Gauge, Steel, Plastic, Welded, Threaded. Rows for Casing (6" 1 65 250) and Liner (4 1/2 5 260).

Final location of shoe(s) \_\_\_\_\_

(7) PERFORATIONS/SCREENS: [X] Perforations Method Saw [ ] Screens Type \_\_\_\_\_ Material \_\_\_\_\_

Table with columns: From, To, Slot size, Number, Diameter, Tele/pipe size, Casing, Liner. Row: 200 260 5" 196 1/8.

(8) WELL TESTS: Minimum testing time is 1 hour [ ] Pump [ ] Bailer [X] Air [ ] Flowing Artesian Yield gal/min 100+ Drawdown \_\_\_\_\_ Drill stem at 240 Time 1 hr.

Temperature of Water 54 Depth Artesian Flow Found \_\_\_\_\_ Was a water analysis done? [ ] Yes By whom \_\_\_\_\_ Did any strata contain water not suitable for intended use? [ ] Too little [ ] Salty [ ] Muddy [ ] Odor [ ] Colored [ ] Other \_\_\_\_\_ Depth of strata: \_\_\_\_\_

(9) LOCATION OF WELL by legal description: County Yamhill Latitude \_\_\_\_\_ Longitude \_\_\_\_\_ Township 55 N or S. Range 6W E or W, WM. Section 29 NE 1/4 SE 1/4 Tax Lot \_\_\_\_\_ Lot \_\_\_\_\_ Block \_\_\_\_\_ Subdivision \_\_\_\_\_ Street Address of Well (or nearest address) 20950 Rock Cr. Rd. Sheridan, OR.

(10) STATIC WATER LEVEL: 68 ft. below land surface. Date 2-31-94 Artesian pressure \_\_\_\_\_ lb. per square inch. Date \_\_\_\_\_

(11) WATER BEARING ZONES: Depth at which water was first found 6'

Table with columns: From, To, Estimated Flow Rate, SWL. Rows: 6' 40' 20 6', 238 250 100+ 68'.

(12) WELL LOG: Ground elevation \_\_\_\_\_

Table with columns: Material, From, To, SWL. Rows include Clay Black 0 6, Clay Stone Brown 6 40, Clay Stone Sandy Gray 40 210, Clay Stone Sandy Dark Gray 210 217, Clay Stone Sandy Gray 217 234, Sandstone (Med) Gray 234 250 68', Sandstone (Hard) Gray 250 252, Clay Stone Sandy Gray 252 260.

RECEIVED

MAR 20 1994

WATER RESOURCES DEPT. SALEM, OREGON

Date started 1-27-94 Completed 2-31-94

(unbonded) Water Well Constructor Certification: I certify that the work I performed on the construction, alteration, or abandonment of this well is in compliance with Oregon well construction standards. Materials used and information reported above are true to my best knowledge and belief. WWC Number \_\_\_\_\_ Signed \_\_\_\_\_ Date \_\_\_\_\_

(bonded) Water Well Constructor Certification: I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon well construction standards. This report is true to the best of my knowledge and belief. WWC Number 1563 Signed Dan McCall Date 2-14-94