

RECEIVED

AUG 23 1994

55/4w/14dc

yamh
3164

AMENDED

State of Oregon
WATER WELL DRILLERS REPORT (as required by ORS 537.765)

Page 1 of 2 WATER RESOURCES DEPT Card # 26316

(1) OWNER: Well No. 1456
Name TERRY/MARTHA CANNON
Address 9165 SE HILLVIEW DR.
City AMITY St OR Zip 97101

(2) TYPE OF WORK: NEW WELL

(3) DRILL METHOD: ROTARY AIR

(4) PROPOSED USE: IRRIGATION / DOMESTIC

(5) BORE HOLE CONSTRUCTION:
Special Construction Approval: NO Depth of Compl. Well 420 ft
Explosives used NO Type Amount
MOLE SEAL
Dian. From To Material From To Amount
10 0 39 BENTONITE 0 39 11 S&T
6 39 420

Seal placement method OTHER, POURED

Backfill: from ft to ft Material
Gravel: from ft to ft Size

(6) CASING/LINER:
Dian. From To Gauge Material Connection
Casing 6 +1 39 .25 STEEL WELDED

Liner 4 0 420 160# PLASTIC WELDED

Final Location of shoe(s)

(7) PERFORATIONS/SCREENS:
 Perforations Method ELECTRIC SAW
 Screens Type Material
Slot Tele/pipe
From To Size Number Dian. size Casing/liner
380 420 6" 72 LINER

(8) WELL TESTS: Minimum testing time is 1 hour

Test type AIR
Yield GPM Draw-down Drill stem at Time
60 _____ 420 1 hr.

Temperature of water 54 Depth Artesian Flow Found
Was water analysis done? NO By whom _____
Reason for water not suitable for use
Depth of strata 0

(9) LOCATION OF WELL by legal description:
SALEM, OREGON
County YAMHILL Lat. 45° 07' 58" Long. 123° 08' 35"
Township 5 S Range 4 W
Section 14 SW 1/4, SE 1/4
Tax Lot Lot Block Subdivision
Street Address of Well (or nearest Address)
9140 SE HILLVIEW DR AMITY, OR

(10) STATIC WATER LEVEL:
216 ft. below land surface. Date 08/11/94
Artesian pressure psi Date

(11) WATER BEARING ZONES:
Depth at which water was first found 391
From To Est Flow Rate SWL
391 410 60 216

(12) WELL LOG:
Material Ground elevation From To SWL
TOP SOIL 0 4
RED CLAY 4 17
BROWN CLAY 17 24
DECAYED BASALT 24 30
HARD GRAY BASALT 30 81
MEDIUM GRAY BASALT 81 133
RED DECAYED BASALT 133 136
HARD GRAY BASALT 136 190
SLIGHTLY DECAYED BASALT 190 191
HARD GRAY BASALT 191 202
DECAYED POROUS BASALT 202 210
HARD GRAY SHALE 210 391
HARD BROKEN SHALE 391 410 216
HARD GRAY SHALE 410 420

DAVE PAYSINGER
BLUE WATER DRILLING CO.
Date started 08/09/94 Completed 08/11/94

(unbonded) Water Well Constructor Certification: I certify that the work I performed on the construction, alteration or abandonment of this well is in compliance with Oregon well construction standards. Materials used and information reported above are true to my best knowledge and belief.
Signed _____ WWC Number _____
Date _____

(bonded) Water Well Constructor Certification: I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction date reported above. All work performed during this time is in compliance with Oregon well construction standards. This report is true to the best of my knowledge and belief.
Signed *David B. Paysinger* WWC Number 1438
Date 08/11/94

YAMH
3164

RECEIVED

55/4w/14 dc

State of Oregon
WATER WELL DRILLERS REPORT (as required by ORS 537.765) Page 1 of 2

Start Card # 26316

WATER RESOURCES DEPT.
SALEM, OREGON

(1) OWNER:
Name TERRY/MARTHA CAMERON
Address 9165 SE HILLVIEW DR.
City AMITY St OR Zip 97101

(9) LOCATION OF WELL by legal description:
County YAMHILL Lat. 45° 07' 58" Long: 123° 08' 35"
Township 5 S Range 4 W
Section 14 SW 1/4 SE 1/4
Tax Lot Lot Block Subdivision
Street Address of Well (or nearest Address)
9165 SE HILLVIEW LN AMITY, OR

(2) TYPE OF WORK: NEW WELL

(3) DRILL METHOD: ROTARY AIR

(4) PROPOSED USE: DOMESTIC

(10) STATIC WATER LEVEL:
216 ft. below land surface. Date 08/11/94
Artesian pressure psi Date

(5) BORE HOLE CONSTRUCTION:
Special Construction Approval: NO Depth of Compl. Well 420 ft
Explosives used NO Type Amount
Diam. From To Material SEAL From To Amount
10 0 39 BENTONITE 0 39 11 S&X
6 39 420

(11) WATER BEARING ZONES:
Depth at which water was first found 391
From To Est Flow Rate SWL
391 410 60 216

Seal placement method OTHER, POURED
Backfill: from ft to ft Material
Gravel: from ft to ft Size

(12) WELL LOG:
Material Ground elevation From To SWL
TOP SOIL 0 4
RED CLAY 4 17
BROWN CLAY 17 24
DECAYED BASALT 24 30
HARD GRAY BASALT 30 81
MEDIUM GRAY BASALT 81 133
RED DECAYED BASALT 133 136
HARD GRAY BASALT 136 190
SLIGHTLY DECAYED BASALT 190 191
HARD GRAY BASALT 191 202
DECAYED POROUS BASALT 202 210
HARD GRAY SHALE 210 391
HARD BROKEN SHALE 391 410 216
HARD GRAY SHALE 410 420

(6) CASING/LINER:
Diam. From To Gauge Material Connection
Casing 6 +1 39 .25 STEEL WELDED
Liner 4 0 420 160# PLASTIC WELDED
Final Location of shoe(s)

DAVE PAYSINGER
BLUE WATER DRILLING CO.
Date started 08/09/94 Completed 08/11/94

(7) PERFORATIONS/SCREENS:
[X] Perforations Method ELECTRIC SAW
[] Screens Type Material
Slot Tele/pipe.
From To Size Number Diam. size Casing/liner
380 420 6" 72 LINER

(unbonded) Water Well Constructor Certification: I certify that the work I performed on the construction, alteration or abandonment of this well is in compliance with Oregon well construction standards. Materials used and information reported above are true to my best knowledge and belief.
WVC Number _____
Signed _____ Date _____

(8) WELL TESTS: Minimum testing time is 1 hour
Test type AIR
Yield GPM Draw-down Drill stem at Time
60 _____ 420 1 hr.
Temperature of water 54 Depth Artesian Flow Found
Was water analysis done? NO By whom _____
Reason for water not suitable for use _____
Depth of strata 0

(bonded) Water Well Constructor Certification: I accept responsibility for the construction, alteration, or abandonment of work performed on this well during the construction date reported above. All work performed during this time is in compliance with Oregon well construction standards. This report is true to the best of my knowledge and belief.
WVC Number 1458
Signed *Dave Paysinger* Date 08/11/94