The original and first copy of this report are to be filed with the STATE ENGINEER, SALEM, OREGON 97410 V 23 1970 WE asset type or print) within 30 days from the date of well completion. STATE ENGINEER, SALEM, OREGON 97410 V 23 1970 We will completion. STATE ENGINEER, SALEM, OREGON 97410 V 23 1970 STATE ENGINEER, SALEM, OREGN 97410 V 23 1970 STATE E

State Well No.

State Permit No.

SALEM. ORLGON	1100
(1) OWNER:	(10) LOCATION OF WELL:
Name Col dayer	County Gambille Driller's well number 70/6
Address Shall Sty 420	14 Section 12 T. 35 R. 3W W.M.
(2) TYPE OF WORK (about):	Bearing and distance from section or subdivision corner
(2) TYPE OF WORK (clieck): New Well & Deepening Reconditioning Abandon	
New Well Deepening Reconditioning Abandon II If abandonment, describe material and procedure in Item 12.	F2
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.
	Depth at which water was first found ft.
Cable K Jetted Domestic M Industrial Municipal Dug Bored Irrigation M Test Well Other	Static level / 8 ft. below land surface. Date /0 - 15 70
	Artesian pressure lbs. per square inch. Date
5) CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing
8 "Diam from 0 ft to 1.5.2 ft Gage 1.25"	Depth drilled 150-6 ft. Depth of completed well 150 ft.
"Diam from the form of the Gage The Diam from 2 obour grow ft. Gage	Formation; Describe color, texture, grain size and structure of materials;
"Diam. from ft. to ft. Gage	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in
6) PERFORATIONS: OPErforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.
Type of perforator used torck	MATERIAL From To SWL
Size of perforations of in. by 6 in.	top 03
/60 perforations from 132 ft. to 152 ft.	Brown Copy 3 /2
perforations from ft. to ft.	Brown glattly Clay 12 20
perforations from ft. to ft.	Blue tilty Clay 20 33
(7) SCREENS: Well screen installed? Yes No.	Alax Clay- 33 35
W = 10000 = 1000 = 1000 = 1000 = 1000 = 10000 = 10000 = 10000 = 10000 =	Brown Clay 35 43
Manufacturer's Name	How dry Brown gritty Clay 43 90
Type Model No.	100000000000000000000000000000000000000
Diam. Slot size Set from ft. to ft. Diam. Slot size Set from ft. to ft.	Maral with Sandley 114-125
Det Aut management 16. Williams 16.	100 100 100 125 12-1
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	and Bour Clas-
Was a pump test made? M Yes No If yes, by whom?	Hord 1000 150 150'6"
74 74	100 000
Yield: 30 gal./min. with 8 Lft. drawdown after 76 hrs.	
" " " " " " " " " " " " " " " " " " " "	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1
n n n	VII / 1975 /
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	
temperature of water Depth artesian flow encountered ft.	Work started 10-7 1970 Completed 10-27 1970
(9) CONSTRUCTION: Spudded in my 8 tot	Date well drilling machine moved off of well 10-15 1970
Well seal-Material used Clay & Bentonite	Drilling Machine Operator's Certification:
Well sealed from land surface toft.	This well was constructed under my direct supervision. Materials used and information reported above are true to my
Diameter of well bore to bottom of sealin.	best knowledge and belief
Diameter of well bore below seal	[Signed] 20 10 mullyn Date 11-16, 19 10
Number of sacks of cement used in well seal sacks	Morilling Machine Operator)
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No
Brand name of bentonite 13.0100	Water Well Contractor's Certification:
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is
Was a drive shoe used? ☐ Yes No Plugs Size: location ft.	true to the best of my knowledge and belief.
Did any strata contain unusable water? Yes No	Name///Person, ripm or corporation) (Type or print)
Type of water? depth of strata	Address Stor Route Box 97 St Haul Dre
Method of sealing strata off	Anil VI D
Was well gravel packed? X Yes ☐ No Size of gravel 74 - 34	[Signed] Mills MeMuster (Water Well Contractor)
70 10	Contractor's License No. 387 Date 11-16 1970
Gravel placed from ft. to ft.	19.74 19.74