NOTICE TO WATER WELL CONTRACTOR.
The original and first copy of this report
are to be filed with the

YAMIWATER WELL REPORT 538 STATE OF OREGON (Please type

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Do not write above this line)

State	Well	No.	3 s /3w-26da	

State	Well No)	3 s 13w	-26 da
State	Permit	No.	***************************************	

(1) OWNER:	(10) LOCATION OF WELL:			
Name // B. HATHUR Fruill	County YAMhi Driller's well number			
Address 910 S.W. alder	NE 14 SE 14 Section 26 T.3 S R. 3 W.M.			
Dunder, Ore. 97/15	Bearing and distance from section or subdivision corner			
(2) TYPE OF WORK (check):	2000 ' N. D BM 190			
New Well				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found /69 ft.			
Rotary Driven Domestic M Industrial Municipal D	Static level 39 ft. below land surface. Date 6/30			
Cable	Artesian pressure ————————————————————————————————————			
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing			
673." Diam. from +1 ft. to 77 ft. Gage (250	Depth drilled / & C ft. Depth of completed well / & O ft. Formation: Describe color, texture, grain size and structure of materials;			
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in			
6) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate principal water-bearing strata.			
Type of perforator used	MATERIAL From To SWL			
Size of perforations in. by in.	Red Top Soil 0 7			
perforations from ft. to ft.	CLAY Red 7 60 39			
perforations from ft. to ft.	SANDSTONE, BED BOWN 60 72			
perforations from ft. to ft.	SANDSTUNE, BROWN 72 90			
(E) CODERAIC.	SANdstone, Gray-Brown			
(7) SCREENS: Well screen installed? Yes No	w/ Busult Boulders			
Manufacturer's Name	BASalt Gray Hard 120 132			
Type Model No. ———————————————————————————————————	BANDSTUNE, Brown 132 152			
Diam. Slot size Set from ft. to ft.	BASALT Gray HAVE 152 160			
	1700			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Enkiunitred Water			
Was a pump test made? ☐ Yes No If yes, by whom?	at 10910 DEFFER			
Yield: gal./min. with ft. drawdown after hrs.	<u> </u>			
a " " "	4UCC - 7079			
" " "	WATER RESOURCES DEPT			
Filer test /CC gal./min. with 80ft. drawdown after 2 hrs.	SALEM, OREGON			
Artesian flow g.p.m.	CALLELINI, OREGON			
mperature of water 53 Depth artesian flow encountered ft.	Work started 6/29 19/19 Completed 7/3 19/79			
(9) CONSTRUCTION:	Date well drilling machine moved off of well 7/4. 1979			
Well seal—Material used Cemen T	Drilling Machine Operator's Certification:			
Well sealed from land surface to	This well was constructed under my direct supervision.			
Diameter of well bore to bottom of seal	Materials used and information reported above are true to my best knowledge and belief.			
Diameter of well bore below seal	[Signed] Thomas E. Bryant Date 7/3, 1929			
Number of sacks of cement used in well sealsacks	(Drilling Machine Operator)			
How was cement grout placed? Grown Auro	Drilling Machine Operator's License No.			
not annales space than great	Water Well Contractor's Certification:			
fipe	y. y.,			
N. A.	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.			
Was a drive shoe used? Yes No Plugs Size: location ft.	Name BYYANT Well Drilling			
Did any strata contain unusable water? Yes V No	(Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address Mi A Dex 18th Number 014 1115			
Method of sealing strata off	[Signed] Whomas 2. Myans			
Was well gravel packed? ☐ Yes X No Size of gravel:	(Water Well Contractor)			
Gravel placed from ft. to ft.	Contractor's License No. 763 Date 73 19			