NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
SALEM, OREGON 97310
within 30 days from the date
of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)

(Do not write above this line)

YAMM	State Well No. 35/3 W - 26
	State Permit No.

(1) OWNER: Name FRANK STILLER	(10) LOCATION OF WELL: County / Qm h; // Driller's well n	umber	63 a	8
Address PT 2	14 14 Section 2 (o T. 3 S	R. 31	11	W.M.
Yamhill, OR	Bearing and distance from section or subdivis.			***************************************
(2) TYPE OF WORK (check):	Dearing and distance ream section of substants	ion come.		
New Well Deepening □ Reconditioning □ Abandon □				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	roll		***************************************
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	375		
Rotary M Driven D		<u> </u>		127
Cable	Static level 300 ft. below land Artesian pressure lbs. per squa			<u>(2) /</u> /
CASING INSTALLED: Threaded Welded W	(12) WELL LOG: Diameter of well			5 //
4 " Diam. from 0 ft. to 510 ft. Gage 160	Depth drilled S/O ft. Depth of comp		$ \sim$ $^{\prime}$ $^{\prime}$	9 ft.
"" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and show thickness and nature of each stratu with at least one entry for each change of forms	ım and ac	quifer pe	enetrated,
PERFORATIONS: Perforated? Y Yes \(\square\) No.	position of Static Water Level and indicate pri			
Type of perforator used SAW	MATERIAL	From	то	swL
Size of perforations /4 in. by 6 in.	TOP Soil	10	3	
30 perforations from 320 ft. to 370 ft.	Red C/AY	3.	10	
50 perforations from 470 ft. to 5/0 ft.	SAND STONE	130	30	
perforations from ft. to ft.	Soft Rock	30	80	
(7) SCREENS: Well screen installed? Yes No	HARA ROLL	30	240 310	
Manufacturer's Name	Soft BROKEN ROCK	3/1	375	
Type Model No.	white Clay	375	357	
Diam ft. to ft.	soft Rock	330	380	
Diam Slot size Set from ft. to ft.	HARD ROCK	380	460	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	soft Rock	460	500	
Was a pump test made? Wes I No If yes, by whom? DRIVER	HARD ROCK	300	5/0	
Was a pump test made? Si ves 1 No 11 yes, by whom? \(\text{K} \) \(\text{Viol} \) \(\text{Viol} \)	RECEIVER			
" " "	- TIVED	1		
" " "	JUN 2.5 1979			
Bailer test gal./min. with ft. drawdown after hrs.	WATER RESOURCES DEPT	 		
Artesian flow g.p.m.	SALEM, OREGON	1		
perature of water 52 Depth artesian flow encountered ft.	Work started 6 - 7 1979 Complete	ed 6 -	13	197 9
(9) CONSTRUCTION:	Date well drilling machine moved off of well	6-	13	1979
Well seal-Material used Cement grout	Drilling Machine Operator's Certification	:		
Well sealed from land surface to 9.5 ft.	This well was constructed under my direct supervision.			
Diameter of well bore to bottom of seal in.	Materials used and information reported above are true to my best knowledge and belief.			
Diameter of well bore below seal	[Signed] Muha Boralulie	Date .	21	19.79
Number of sacks of cement used in well sealsacks	(Drilling Machine Sperator)	/) 7	7 7	.,
How was cement grout placed? Pumped	Drilling Machine Operator's License No.	k.beek.		
	Water Well Contractor's Certification:		11.00	She had a
	This well was drilled under my jurisd true to the best of my knowledge and be	iction an lief.	d this r	eport is
Was a drive shoe used? Yes No Plugs Size: location ft.	Name BIUC WATER D	P: 1	line	5 C
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Ty	pe or pri	7
Type of water? depth of strata	Address K. I. I. S. J. J. J. J.	100	2	7
Method of sealing strata off	[Signed] Robert Shell	lies	ns	
Was well gravel packed? Yes No Size of gravel:	(Water Well Cont	ractor)	12	70
Gravel placed from ft. to ft.	Contractor's License No. 7.1 Date	$\frac{1-\alpha}{2}$	<u> </u>	, 19//