STATE ENGINEER, SALEM, OREGON 97310 455/ within 30 days from the date of well completion.

(Please type or pring TATE ENGINETERMIT No. (Do not write above this line) ALEM. OREGON

(1) OWNER:	(10) LOCATION OF WELL:	y ==	
Name City of Dundee	County Yamhill Driller's well nu		
Address Dundee, Oregon	14 14 Section 27 T. 3 S	R. 3	W. W.M.
1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	Bearing and distance from section or subdivision	on corner	
(2) TYPE OF WORK (check):			
New Well ☎ Deepening ☐ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	الم	
(3) TYPE OF WELL: (4) PROPOSED USE (check):		16	ft.
	Depth at which water was first found		2/8/72
Rotary M Driven D Domestic I Industrial Municipal M Domestic I Industrial D Municipal M Irrigation D Test Well D Other	Static level 0 ft. below land s Artesian pressure lbs. per squar		3/0/13
(5) CASING INSTALLED: Threaded Welded Z	400	,	8 u
8 " Diam. from 0 ft. to 40 ft. Gage •250	(12) WELL LOG: Diameter of well b	_	
	Depth drilled 200 ft. Depth of compl	eted well	200 ft.
" Diam, fromft. toft. Gage	Formation: Describe color, texture, grain size a	and structure	of materials;
" Diam. fromft. toft. Gage	and show thickness and nature of each stratur with at least one entry for each change of format	n and aquifer tion. Report ec	penetrated, ich change in
(6) PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate prin	cipal water-be	aring strata.
Type of perforator used	MATERIAL	From To	o SWL
	Red-brown clay	0	<u>li</u>
	Weathered brown basalt with		
perforations fromft. toft.	brown clay seams	1 1	.6
perforations fromft. toft.	Broken brown basalt-water		
perforations fromft, toft.	bearing. occ. hard streak		
(7) SCREENS: Well screen installed? Yes Yes No	of gray-black basalt	16 6	35
Manufacturer's Name	Visicular red-brown basalt		38
Type	Broken brown basalt w/brown	 	
Diam. Slot size Set from ft. to ft.	soapstone .	68 8	30
Diam. Slot size Set from ft. to ft.	Broken gray-black basalt -	† <u> </u>	
	waterbearing	80 8	35
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	Broken gray-black and brown		
	basalt - waterbearing	85 10	15
Was a pump test made? ☐ Yes ☒ No If yes, by whom?	Hard gray-black basalt	105 11	- · · · · · · · · · · · · · · · · · · ·
: gal./min. with ft. drawdown after hrs.	Fractured gray-brown basalt		
n n	waterbearing	110 12	20
// // // // // // // // // // // // //	Hard fractured gray-black		
airlift 100 gal./min. with 160 ft. drawdown after 2 hrs.	basalt - waterbearing	120 16	55
sian flow g.p.m.	Broken gray basalt-hard	165 17	70
mperature of water Depth artesian flow encountered ft.	Work started 2/28/73 19 Complet	ed 3/8/73	3 19
manipotantic of water Deput assistant now chroatesta manifestation for	Date well drilling machine moved off of well	3/8/73	19
(9) CONSTRUCTION:			
Well seal—Material used Cement	Drilling Machine Operator's Certification:		t
Well sealed from land surface to	This well was constructed under my Materials used and information reported	above are	true to my
Diameter of well bore to bottom of seal $\frac{12}{\Omega}$ in.	best knowledge and belief.		
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)	Date3/9,	<u>/.7.3 ,</u> 19
Number of sacks of cement used in well seal10sacks	Drilling Machine Operator) Drilling Machine Operator's License No.	523	
Number of sacks of bentonite used in well seal sacks	Driffing Machine Operator's License No.	· · · · · · · · · · · · · · · · · · ·	
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons	This well was drilled under my jurisd	liction and th	nis report is
of water lbs./100 gals.	true to the best of my knowledge and be	lief.	
Was a drive shoe used? \square Yes $\stackrel{\mathbf{L}}{\square}$ No Plugs Size: location ft.	Name A. M. Jannsen Drilling	Co.	
Did any strata contain unusable water? Yes No	(Dorgon firm or comporation)	(Type o	r print)
Type of water? depth of strata	Address 21075 S.W.Tualatin Vall	rey nwy.	ore other
Method of sealing strata off	Isimal Dull	muse	.
Was well gravel packed? ☐ Yes ☒ No Size of gravel:	[Signed] (Water West Cont	ractor)	
	Contractor's License No		19
Gravel placed from ft. to ft.	<u> </u>		SP*45656-119
(IISE ADDITIONAL S)	HEETS IF NECESSARY)		DE-#00000-118

NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be Alled with the

STATE FINGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)



State Well No.

State	Permit	No.	NAME OF THE OWNER

(Do not write above this line)

	(10) I OCATION OF WELL.		
(1) OWNER:	(10) LOCATION OF WELL:		
Name City of Dundee Page 2	County Driller's well number		
Address	1/4 Section T. R.	W.M.	
The second secon	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	The second secon		
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	ft.	
Rotary Driven Domestic Industrial Municipal	Static level ft. below land surface. Date	e	
Cable			
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date	-	
(5) CASING INSTALLED:Threaded [] Welded []	(12) WELL LOG: Diameter of well below casing		
" Diam. from ft. to ft. Gage			
" Diam, fromft. toft. Gage	Formation: Describe color, texture, grain size and structure	of materials:	
" Diam. fromft. toft. Gage	and show thickness and nature of each stratum and aquif	er penetrated,	
	with at least one entry for each change of formation. Report position of Static Water Level and indicate principal water-	zach change in bearing strata.	
(6) PERFORATIONS: Perforated? Yes No.			
Type of perforator used	MILLIANTE	To SWL	
Size of perforations in by in.	Di Onori Di Onir di Barri	88	
perforations fromft. toft.	Hard gray basalt 188 2	.00	
perforations fromft. toft.			
perforations fromft. toft.			
(7) SCREENS: Well screen installed? Yes No			
Manufacturer's Name			
Type Model No.			
Diam. Slot size Set from ft. to ft.			
Diam. Slot size			
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
· ·			
Was a pump test made? Yes No If yes, by whom?			
: gal./min. with ft. drawdown after hrs.		:	
$\frac{n}{n}$			
n n			
Bailer test gal./min. with ft. drawdown after hrs.			
sian flow g.p.m.			
	Work started 19 Completed	19	
Emperature of water Depth artesian flow encountered	•	19	
(9) CONSTRUCTION:	Date well drilling machine moved off of well		
	Drilling Machine Operator's Certification:		
Well seal—Material used	This well was constructed under my direct s Materials used and information reported above are	upervision.	
Diameter of well bore to bottom of seal in.	best knowledge and belief.	, шас во 1115	
Diameter of well bore below sealin.	[Signed] Date	19	
Number of sacks of cement used in well seal sacks	(Drilling Machine Operator)	•	
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.		
Brand name of bentonite			
Number of pounds of bentonite per 100 gallons	Water Well Contractor's Certification:		
of water lbs./100 gals.	This well was drilled under my jurisdiction and true to the best of my knowledge and belief.	this report is	
Was a drive shoe used? Yes No Plugs Size: location ft.	·		
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation) (Type	or print)	
	Address		
Type of water? depth of strata			
Method of sealing strata off	[Signed](Water Well Contractor)		
Was well gravel packed? Yes No Size of gravel:			
Gravel placed from ft. to ft.	Contractor's License No Date	19	