

The original and first copy of this report are to be filed with the

RECEIVED WATER WELL REPORT STATE OF OREGON

YAMHILL 4589

State Well No. 35/3W-30

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

AUG 4 1977 (Please type or print) (Do not write above this line)

State Permit No.

WATER RESOURCES DEPT.

(1) OWNER: SALEM, OREGON Name The Trappist Foundation Address Lafayette, Ore. 97127

(10) LOCATION OF WELL: County Yamhill Driller's well number 7713 1/4 1/4 Section 30 T. 3S R. 3W W.M. Bearing and distance from section or subdivision corner

(2) TYPE OF WORK (check): New Well XXX Deepening Reconditioning Abandon

(11) WATER LEVEL: Completed well. Depth at which water was first found Static level 47 ft. below land surface. Date 6-8-77 Artesian pressure

(3) TYPE OF WELL: (4) PROPOSED USE (check): Rotary Driven Cable Jetted Dug Bored Domestic Industrial Municipal Irrigation Test Well Other

(12) WELL LOG: Diameter of well below casing Depth drilled 167 ft. Depth of completed well 166'7 3/4"

CASING INSTALLED: Threaded Welded 10" Diam. from 42 ft. to 166'7 3/4 ft. Gage 279

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation.

PERFORATIONS: Perforated? Yes No Type of perforator used torch Size of perforations 3/8 in. by 6 in. 380 perforations from 126'11 3/4" to 166'7 3/4"

Table with columns: MATERIAL, From, To, SWL. Content: See sheet attached

(7) SCREENS: Well screen installed? Yes No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

Work started 3-15-1977 Completed 7-11-1977 Date well drilling machine moved off of well 7-11-1977

(8) WELL TESTS: Drawdown is amount water level is lowered below static level Was a pump test made? Yes No If yes, by whom? driller Yield: 4 gal./min. with 115 ft. drawdown after 48 hrs.

Drilling Machine Operator's Certification: This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief. [Signed] Donald G. Davis Date 7-26, 1977 Drilling Machine Operator's License No. 1085

(9) CONSTRUCTION: Well seal—Material used Cement grout Well sealed from land surface to 40 ft. Diameter of well bore to bottom of seal 18 in. Diameter of well bore below seal 18 in. Number of sacks of cement used in well seal 56 sacks Number of sacks of bentonite used in well seal 0 sacks Brand name of bentonite Number of pounds of bentonite per 100 gallons of water Was a drive shoe used? Yes No Plugs Size: location ft. Did any strata contain unusable water? Yes No Type of water? depth of strata Method of sealing strata off Was well gravel packed? Yes No Size of gravel: 3/4-1 Gravel placed from 40 ft. to bottom ft.

Water Well Contractor's Certification: This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief. Name Schneider Equipment, Inc. Address Rt. 1, Box 97, St. Paul, Ore. 97137 [Signed] Stephen J. Schneider Date 7-26, 1977 Contractor's License No. 649 Date 7-26, 1977

RECEIVED

AUG 4 1977

7713

The Trappist Foundation

WATER RESOURCES DEPT.

SALEM, OREGON

Material

From To

Material	From	To
Top soil, brown	0	8
Clay, brown & gray	8	11
Sandstone, rusty brown sandy hard	11	15
Claystone, dark gray hard	15	18
Sandstone, dark gray fine	18	33
Sandstone, black fine	33	36
Sandstone, medium coarse	36	39
Claystone, dark green	39	41
Clay, gray hard	41	45
Sandstone, gray fine	45	54
Clay, dark gray hard	54	62
Clay, gray softer	62	65
Sandstone, fine hard	65	77
Rock, light gray w/ streaks fine sandstone	77	78
Sandstone, fine hard dry	78	93
Sandstone, fine hard dry w/ streaks clay	93	106
Claystone, gray hard w/ streaks soft	106	123
Claystone, green hard w/ more soft streaks	123	132
Clay, blue green w/ hard streaks	132	143
Clay, blue green hard & soft mixed	143	147
Clay, gray sandy fine	147	155
Sand, light gray fine	155	163
Clay, gray sandy	163	163'6"
Sand, gray fine	163'6"	165
Clay, gray sandy	165	166
Rock, light gray hard & sandstone	166	167