The original and first copy of this report are to be filed with the JAN26 1979

WATER WELL REPORT

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON PRESOURCES DEPTease type or print) of well completion.

SALEM, OREGON Do not write above the completion. SALEM, OREGON(Do not write above this line)

YA MH	State Well No. 35/30	u-33,
4625	State Permit No	

	<b>∀</b>		
(1) OWNER:	(10) LOCATION OF WELL:		
Name Ron Brown	County Yamhill Driller's well n	umber 279	
Address Rt.2 Box 219	SW 14 SE 14 Section 33 T. 3S	R. 3W W.M	
Dayton, Oregon	Bearing and distance from section or subdivis	ion corner	
(2) TYPE OF WORK (check):			
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐			
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	zell.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 210		
Rotary M Driven D Domestic M Industrial Municipal D		surface. Date 12/21/	
Cable   Jetted   Jones   Industrial   Industrial   Dug   Bored   Irrigation   Test Well   Other	-	re inch. Date	
CASING INSTALLED: Threaded   Welded	(12) WELL LOG: Diameter of well below casing		
6 "Diam from +1 ft. to 166 ft. Gage .250	Depth drilled 258 ft. Depth of comp	<u> </u>	
4 P.V.Clam. from 0 ### ft. to 258 ft lags 125	Formation: Describe color, texture, grain size		
" Diam, from ft. to ft. Gage	and show thickness and nature of each stratu	m and aquifer penetrate	
PERFORATIONS: Perforated? \( \frac{1}{2} \) Yes \( \pi \) No.	with at least one entry for each change of forma position of Static Water Level and indicate prin		
Type of perforator used Saw	MATERIAL	From To SWL	
	Top soil	0 1	
te of perforations 1/8 in. by 8 in.  64 perforations from 219 ft. to 257 ft.	Yellow decomposed rock	1 42	
perforations from 2.12 ft. to 2.21 ft.	Soft brown rock	42 148	
perforations from	Soft black rock	148 152	
perforations from	Medium brown rock	152 180	
(7) SCREENS: Well screen installed?   Yes X No	Med. black rock	180 188	
Manufacturer's Name	Med. brownbasalt	188 230	
Type Model No Model No.	Med. black rock	230 254	
Diam Slot size Set from ft. to ft.	Gray shale	254 256	
Diam. Slot size Set from ft. to ft.	Soft black rock	256 258	
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? 🗆 Yes XVNo If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " "			
ailer test gal./min. with ft. drawdown after hrs.			
rtesian flow g.p.m.	<del>,</del>	<del></del>	
mperature of water Depth artesian flow encountered ft.	Work started \ \ \]/20/78 19 Complet	ed ] 2/21/78 19	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	12/21/78 19	
Vell seal-Material used Cement grout	Drilling Machine Operator's Certifications		
Well sealed from land surface to60' ft.	This well was constructed under my Materials used and information reported		
Diameter of well bore to bottom of seal in.	best knowledge and belief		
Diameter of well bore below seal8 in.	[Signed] Led Khalekar	Date 1-22, 19	
Number of sacks of cement used in well seal 9 sacks	(Drilling Machine Operator)  Drilling Machine Operator's License No.		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		
Brand name of bentonite	Water Well Contractor's Certification:	v	
Number of pounds of bentonite per 100 gallons		iction and this report	
of water lbs./100 gals.	This well was drilled under my jurisd true to the best of my knowledge and be		
Was a drive shoe used? ☐ Yes ဩ No Plugs Size: location ft.	Name Ted Schueler Well Di	rilling	
Did any strata contain unusable water?   Yes \ No	(Person, firm or corporation)	(Type or print)	
Type of water? depth of strata	Address Rt. Box 387 Dundee	oregon	
Method of sealing strata off	[Signed] Thuslay W hh	enly	
Was well gravel packed? X Yes No Size of gravel:3/8	(Water Well Cont	ractor)	
Gravel placed from 60 ft. to 258 ft.	Contractor's License No Date	12- 19/	