NOTICE TO WATER WELL CONTRACTOR
The priginal and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

YAMWATER WELL REPORT

STATE OF OREGON
(Please type or print)

(Please type or print)
(Do not write above this line)

State	Well	No.	35/3W-34
-------	------	-----	----------

State Permit No.

		P4		
(1) OWNER:	(10) LOCATION OF WELL:			
Name WALT LOS 9015T JR	County /am h.' // Driller's well number 642			
Address 1952 FGANWAY	14 14 Section 34 T. 35 R. 3W W.M.			
LAKE BSWEGO OR 97034	Bearing and distance from section or subdivis	ion corne	r	
(2) TYPE OF WORK (check):				
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐				
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.			
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found	L T C)	ft.
Rotary Driven Domestic Andustrial Municipal Domestic	Static level 275 ft. below land	surface.	Date D	cely 5-7
Dug Bored Irrigation Test Well Other	Artesian pressure lbs. per squa	re inch.	Date	
CASING INSTALLED: Threaded Welded				
CASING INSTALLED: Threaded Welded Welded ft. to ft. Gage -255	(12) WELL LOG: Diameter of well		•	e
4 "Diam. from 5 ft. to 455 ft. Gage 160 #	Depth drilled 455 ft. Depth of completed well 455 ft.			
	Formation: Describe color, texture, grain size	and struc	ture of n	naterials;
	and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in			
PERFORATIONS: Perforated? Yes 4 No.	position of Static Water Level and indicate prin	ncipal wa	ter-bearin	g strata.
Type of perforator used	MATERIAL	From	То	SWL
Size of perforations in. by in.	TOP Soil	0	4	
perforations from ft. to ft.	RED CIAY	4	30	
perforations from ft. to ft.	SOFT PED ROCK	30	60	
perforations from ft. to ft.	SOFT BROWN POCK	20	200	
(7) SCREENS: Well screen installed? Yes	med drey pock	200	240	
Manufacturer's Name	HARD GREY ROCK	240	310	
Type Model No	Red Broken Rock	310	335	
Diam Slot size Set from ft. to ft.	HAROG REY ROCK	325	455	-
Diam. Slot size Set from ft. to ft.				
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	CEPENER	 		
Was a pump test made? Dives No If yes, by whom?	- KELFIYES	 		
Yield: 25 gal./min. with 100 ft. drawdown after 1 hrs.	JUL 171979	1		
gar, mar. with por it. drawdown after t mis.	- WATER RESOURCES DEPT			····
" " "	SALEM, OREGON			
The United States and Advantage Control of the Cont	SALEM, ONEGON			
And all all all all all all all all all al		ļ!		
perature of water Depth artesian flow encountered	Work started 6 - 2 9 1979 Complete	——		79
perdure of water Depth artesian now encountered		ed /	- 6	19/
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7-	4	19/
Well seal—Material used (muli)	Drilling Machine Operator's Certification			
Well sealed from land surface toft.	This well was constructed under my Materials used and information reported	direct	super are true	vision. to my
Diameter of well bore to bottom of sealin.	best knowledge and belief.		2-11	19
Diameter of well bore below seal	[Signed] (Drilling Machine Operator)			
How was cement grout placed?	Drilling Machine Operator's License No33/			
				
	Water Well Contractor's Certification:			
154 45	This well was drilled under my jurisd		nd this r	eport is
Was a drive shoe used? Yes Plugs Size: location ft.	true to the best of my knowledge and belief.			
Did any strata contain unusable water? Yes No	Name (Person, firm or corporation) (Type or print)			
Type of water? depth of strata	Address RT/BX25 DHYTON	2. OK	حج	•
Method of sealing strata off	[Signed] Ogobert 8	kel.	bue	
Was well gravel packed? [] Yes Size of gravel:	(Water Well Cont	ractor)	······································	
Gravel placed from ft. to ft.	Contractor's License No. 4/7 Date	7-/0	6	., 19 <i>7. J</i>