NOTICE TO WATER WELL CONTRACTOR The original and first copy of this report are to be filed with the

WATER WELL REPORT
STATE OF OREGON

(Please type or print)

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(Do not write above this line)

State	Well No. 35 4W -5
State	Permit No.

(1) OWNER:	(10) LOCATION OF WELL:		
Name CAMPTILLINUM PEULI	County Yamhill Driller's well number		
Address RT.3 BOX 426 NEWBERG ORE	14 14 Section 5 T. 35 R. 44	V- W.M.	
JUN 161090/32	Bearing and distance from section or subdivision corne	4 . 4	
(2) TYPE OF WORK (check):		· () A ()	
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 2N	(11) WATER LEVEL: Completed well.		
(3) TYPE OF WELL: (4) PROPOSED USE (check):	770		
Rotary Driven	1.0	Date 3-20-78	
Cable L Jetted Domestic L Industrial Municipal		Date 3-20-10	
Dug	Artesian pressure lbs. per square inch.	Date	
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below ca	otne 611	
278 ODDiam from 0 ft. to 40 ft. Gage • 250	Ama	Suig	
5 1/2 ODpiam from 35 ft. to 270 ft. Gage			
ft. Gage	Formation: Describe color, texture, grain size and strue and show thickness and nature of each stratum and a		
DEDECOR A MICANO.	with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.		
PERFORATIONS: Perforated? Tyes \(\square\) No.	position of Static Water Level and indicate principal wa	ter-vearing strata.	
Type of perforator used Skill saw	MATERIAL From	To SWL	
Size of perforations 1/8 in. by 6 in.	clay	20	
84 perforations from 40 ft. to 268 ft.	shale 20	28	
ft. to ft.	med hard broken shale 28	35	
perforations from ft. to ft_	shale 35	90	
(7) SCREENS: Well screen installed? I Yes Z No	hard gray shale 90	98	
West bester instituted. In the Earth	shale 98	134	
Manufacturer's Name Type Model No.	brokek dark grey shale water 134	158	
Diam. Slot size Set from ft. to ff.		210	
Diam. Slot size Set from ft. to ft.	shale158stickey shale210	270	
	SOLORGY BURLE		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level			
Was a pump test made? ☐ Yes ☒ No If yes, by whom?			
Yield: gal./min. with ft. drawdown after hrs.			
" " "	The state of the s		
" " " "			
Bailer test 8 gal./min. with tomft. drawdown after 7 hrs.			
		<u> </u>	
Artesian flow g.p.m.	35 0 20		
perature of water Depth artesian flow encounteredft.	Work started Mar 8 1978 Completed M	lar 20 19 78	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	Mar 20 19 78	
Well seal-Material usedCement	Drilling Machine Operator's Certification:		
Well sealed from land surface to 40 ft.	This well was constructed under my direc	t supervision.	
Diameter of well bore to bottom of seal10in.	Materials used and information reported above best knowledge and belief.	are true to my	
Diameter of well bore below seal in.	[Signed] John T // leekpate	3-24 19 78	
Number of sacks of cement used in well seal XXX	(Drilling Machine Operator)	. ,	
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	<u> </u>	
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons			
of waterlbs./100 gals.	This well was drilled under my jurisdiction a true to the best of my knowledge and belief.	na uns report 18	
Was a drive shoe used? Yes X No Plugs No. Size: location ft.	Name JOHN MERKER WELL DRILLING		
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (T	ype or print)	
Type of water? depth of strata	Address 2902/Hoover Blvd, Newberg, C)r 97132	
Method of sealing strata off	[Signed] John & Illee	kel	
Was well gravel packed? Tyes I No Size of gravel:	(Water Well Confractor)	3 - 24 78	
Gravel placed from ft. to ft.	Contractor's License No Date	3 – 24 78	