NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the
WATER RESOURCES DEPARTMENT
SALEM, OREGON 97310
within 30 days from the date of well completion.

WATER WELL REPORT
STATE OF OREGON
(Please type or print)
(Do not write above this line)

RECEIVED
JUL - 5 1977
WATER RESOURCES DEPT.
SALEM, OREGON

YAMH 4796

State Well No. 3s/4w-11cb
State Permit No.

(1) OWNER:
Name Ralph Bunn
Address Rte. 2, McMinnville, Oregon 97128

(2) TYPE OF WORK (check):
New Well ☒ Deepening ☐ Reconditioning ☐ Abandon ☐
If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:
Rotary ☒ Driven ☐
Cable ☐ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):
Domestic ☒ Industrial ☐ Municipal ☐
Irrigation ☐ Test Well ☐ Other ☐

(5) CASING INSTALLED: Threaded ☐ Welded ☒
6" Diam. from 0 ft. to 103 ft. Gage .25
" Diam. from ft. to ft. Gage
" Diam. from ft. to ft. Gage

PERFORATIONS: Perforated? ☒ Yes ☐ No.
Type of perforator used Torch
Size of perforations 1/4 in. by 12 in.
30 perforations from 93 ft. to 103 ft.
perforations from ft. to ft.
perforations from ft. to ft.

(7) SCREENS: Well screen installed? ☐ Yes ☒ No
Manufacturer's Name
Type Model No.
Diam. Slot size Set from ft. to ft.
Diam. Slot size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level
Was a pump test made? ☐ Yes ☒ No If yes, by whom?
Yield: gal./min. with ft. drawdown after hrs.
" " " "
" " " "
Bailer test 25 gal./min. with 45 ft. drawdown after 2 hrs.
Artesian flow g.p.m.
Temperature of water 50 Depth artesian flow encountered ft.

(9) CONSTRUCTION:
Well seal—Material used Cement Grout
Well sealed from land surface to 24 ft.
Diameter of well bore to bottom of seal 12 in.
Diameter of well bore below seal 12 in.
Number of sacks of cement used in well seal 1/2 Yd. grout Mix sacks
How was cement grout placed? Poured from land surface to 24 Ft.
Was a drive shoe used? ☐ Yes ☒ No Plugs Size: location ft.
Did any strata contain unusable water? ☐ Yes ☒ No
Type of water? depth of strata
Method of sealing strata off
Was well gravel packed? ☒ Yes ☐ No Size of gravel: 3/8 Pea
Gravel placed from 24 ft. to 103 ft.

(10) LOCATION OF WELL:
County Yamhill Driller's well number
NW ¼ SW ¼ Section 11 T. 3S R. 4W W.M.
Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.
Depth at which water was first found 78 ft.
Static level 30 ft. below land surface. Date June 23
Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 0
Depth drilled 103 ft. Depth of completed well 100 ft.
Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. **Report each change in position of Static Water Level and indicate principal water-bearing strata.**

MATERIAL	From	To	SWL
Topsoil	0	2	
Red & Yellow Clays	2	42	
Blue Clay	42	78	
Med. Blue Sand & Fine Gravel	78	97	
Blue Clay	97	103	

Work started June 16 1977 Completed June 23 1977
Date well drilling machine moved off of well June 23 1977

Drilling Machine Operator's Certification:
This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.
[Signed] Randall L. Wilcox (Drilling Machine Operator) Date June 28, 1977
Drilling Machine Operator's License No. 991

Water Well Contractor's Certification:
This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.
Name Wilcox Drilling & Pump Co. (Person, firm or corporation) (Type or print)
Address P. O. Box 569, McMinnville, Oregon 97128
[Signed] Jarvis H. Wilcox (Water Well Contractor)
Contractor's License No. 428 Date June 28, 1977

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119