NOTICE TO WATER WELL CONTRACTOR
The original and first copy

of this report are to be filed with the

AMH WATER WELL REPORTE OF THE

AUG 15 197state Well No.

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

STATE OF OREGON

(Please type or print) TATE ENGINEER PRImit No. . (Do not write above this ling / LEM OREGON

(1) OWNER:	(10) LOCATION OF WELL:	91.2
Name Volled Sollinson		nber 262
Address It (ON) 23A	/ 1/4 1/4 Section / 3 T(35 R	2. 4 (U) W.M.
Contra One.	Bearing and distance from section or subdivision corner	
(2) TYPE OF WORK (check):		
New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found 62 ft.	
		C 10 77
Cable		
Dug □ Bored □ Irrigation □ Test Well □ Other □	Artesian pressure lbs. per square	inch. Date
CASING INSTALLED: Threaded Welded	(12) WELL LOG: Diameter of well below casing	
"Diam. fromft. toft. Gage	C.A.	
	Depth drilled ft. Depth of completed well ft.	
" Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated,	
Diani. 110ii	with at least one entry for each change of formation. Report each change in	
PERFORATIONS: Perforated? Yes No.	position of Static Water Level and indicate princi	pal water-bearing strata.
Type of perforator used	MATERIAL	From To SWL
Size of perforations in. by in.	top soil	02
perforations from ft. to ft.	lahour class	28
perforations fromft. toft.	Tiller and shale	8 80
perforations from ft. to ft.		
perforations from ft. to ft.		
(7) SCREENS: Well screen installed? Yes No		
Manufacturer's Name	NT 198	
Type Model No		
Diam Slot size Set from ft. to ft.	<u>-</u>	
Diam Slot size Set from ft. to ft.		
O THE T PECING. Drawdown is amount water level is		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? Yes No If yes, by whom? Willow		
gal./min. with 50 ft. drawdown after / hrs.		
" " " " "		
" " "		
Bailer test gal./min. with ft. drawdown after hrs.		
Artesian flow g.p.m.	2 15 72	6/27
perature of water Depth artesian flow encountered ft.	Work started 5 - 3 19 3 Completes	ر 19 کر - کی ا
(9) CONSTRUCTION:	Date well drilling machine moved off of well	8-/3 19/3
	Drilling Machine Operator's Certification:	,
Well seal—Material used Comments	This well was constructed under my	direct supervision.
wen sealed from fand surface to	Materials used and information reported above are true to my best knowledge and belief.	
Diameter of well bore to bottom of seal in.		
Diameter of well bore below seal in,	(Duilling Machine Operator)	
Number of sacks of cement used in well seal sacks	Drilling Machine Operator's License No. 33	
Number of sacks of bentonite used in well seal sacks		
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons of waterlbs./100 gals.	This well was drilled under my jurisdiction and this report is	
	true to the best of my knowledge and belief.	
Was a drive shoe used? Yes No Plugs Size location ft.	(Person, firm or corporation) (Type or print)	
Did any strata contain unusable water? ☐ Yes ☐ No	Addros PTIBY175 DOYTAN Ore	
Type of water? depth of strata	Address () Addres	
Method of sealing strata off	[Signed] Bobert & lelburne	
Was well gravel packed? Yes No Size of gravel:	(Water Well Contra	actor)
Gravel placed from ft. to ft.	Contractor's License No Date	<u>) -/5 , 19/.5</u>
	The state of the s	