NOTICE TO WATER WELL CONTRACTOR

The original and firs top C E I E WATER WELL REPORT

of this report are top C E I E WATER WELL REPORT

filed with the I I I O - 1971

STATE OF OREGON

STATE ENGINEER, SALEM, OREGON 97310

within 30 days from protect E ENGINEER

of well completion SALEM. OREGON

SALEM. OREGON

_ ; ,

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:	
NameMr. George Stermmer	County Yamhill Driller's well nu	mber
Address Rt. L Box 201 Carlton ORE.	34 14 Section 211 T. 3-S	R.)
	Bearing and distance from section or subdivision	on corner
(2) TYPE OF WORK (check):		
New WelX		
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed w	ا1م
(3) TYPE OF WELL: (4) PROPOSED USE (check):		· · · · · · · · · · · · · · · · · · ·
	Depth at which water was first found 55	ft.
Rotary Driven Domestic Industrial Municipal Cable Detted D		urface. Date 6/23/71
Dug	Artesian pressure Ibs. per squar	e inch. Date
CASING INSTALLED: Threaded □ Welded \(\frac{\frac{1}{2}}{2} \)	(10) THEFT T OC	6
OD "Diam. from 0 ft. to 90 ft. Gage 250	(12) WELL LOG: Diameter of well h	elow casing
" Diam. fromft. toft. Gage	Depth drilled 94 ft. Depth of compl	77
"Diam. fromft. toft. Gage	Formation: Describe color, texture, grain size a	
Diant. Hone	and show thickness and nature of each stratur with at least one entry for each change of format	
PERFORATIONS: Perforated? 🛣 Yes 🗆 No.	position of Static Water Level and indicate prin	cipal water-bearing strata.
Type of perforator usedCutting torch	MATERIAL	From To SWL
Size of perforations $\frac{1}{2}$ in, by $\frac{1}{2}$ in.	Top soil	0 1
16 perforations from 45 ft. to 89 ft.	Yellow clay silt	4 24
perforations fromft. toft.	Blue gray sand stone	24n 94
perforations from	Broken lavers 55-60	
periorations from	\$ 6 gal here	
(7) SCREENS: Well screen installed? ☐ Yes 🖾 No	some small broken layers	
Manufacturer's Name	60 -94 2 Gal.	3)1
Type Model No.		
Diam Slot size Set from ft. to ft.		
Diam Slot size Set from ft. to ft.		
(8) WELL TESTS. Drawdown is amount water level is		
(8) WELL TESTS: Drawdown is amount water level is lowered below static level		
Was a pump test made? ★ Yes □ No If yes, by whom?		-
Yield: gal./min. with ft. drawdown after hrs.		
" " "		
n n n		
At Bottom		
Bailer test 8 gal./min. with ft. drawdown after hrs.	And the second of the second o	
Artesian flow g.p.m.	-	
perature of water Depth artesian flow encountered ft.	Work started 6/21/71 19 Complete	ed 6/23/7 <u>1</u> 19
(9) CONSTRUCTION:	Date well drilling machine moved off of well	6/23/71 19
Well seal-Material used Cemment	Drilling Machine Operator's Certification:	
Well sealed from land surface to ft.	This well was constructed under my Materials used and information reported	above are true to my
Diameter of well bore to bottom of seal 10 in.	best knowledge and belief.	
Diameter of well bore below seal in.	[Signed] John 7 1100	Date 6/23/7,119
Number of sacks of cement used in well seal sacks	(Drilling Magnine Operator)	٠,- الم
Number of sacks of bentonite used in well sealsacks	Drilling Machine Operator's License No.	
Brand name of bentonite	Water Well Contractor's Certification:	
Number of pounds of bentonite per 100 gallons		iction and this renert is
of water lbs./100 gals.	This well was drilled under my jurisd true to the best of my knowledge and bel	ief.
Was a drive shoe used? Yes Plugs Size: locationft.	Name JOHN MEEKER WELL DRILLING	•
Did any strata contain unusable water? Yes No	(Person, firm or corporation)	(Type or print)
Type of water? depth of strata	Address 2002 Moover BLVD. Newborn	COROE.
Method of sealing strata off	() () () () ()	. ku
2/9 2/1.	[Signed] Water Well Control	ractor)
Was well gravel packed? A Yes No Size of gravel 7/0=-3/4	Contractor's License No. •111 Date 6/	