NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

Yamhill 30

WATER WELL REPORT

STATE OF OREGON

RECEIVED
OCT 10 1973
STATE ENGINEER
SALEM, OREGON

(Please type or print)

(Do not write above this line)

State Well No. 4S/4W-32

State Permit No.

(1) OWNER:

Name Dean Carter

Address 848 N Hwy 99W
Mac Mcminnville Ore

(2) TYPE OF WORK (check):

New Well ☑ Deepening ☐ Reconditioning ☐ Abandon ☐

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary ☐ Driven ☐
Cable ☑ Jetted ☐
Dug ☐ Bored ☐

(4) PROPOSED USE (check):

Domestic ☐ Industrial ☐ Municipal ☑
Irrigation ☐ Test Well ☐ Other ☐

CASING INSTALLED:

Threaded ☐ Welded ☑

6 " Diam. from 0 ft. to 91 ft. Gage .250

" Diam. from ft. to ft. Gage

" Diam. from ft. to ft. Gage

PERFORATIONS:

Perforated? ☑ Yes ☐ No.

Type of perforator used Torch

Size of perforations 1/4 in. by 6 in.

240 perforations from 61 ft. to 91 ft.

perforations from ft. to ft.

perforations from ft. to ft.

(7) SCREENS:

Well screen installed? ☐ Yes ☑ No

Manufacturer's Name

Type Model No.

Diam. Slot size Set from ft. to ft.

Diam. Slot size Set from ft. to ft.

(8) WELL TESTS:

Drawdown is amount water level is lowered below static level

Was a ~~pump~~ Compressor test made? ☑ Yes ☐ No If yes, by whom? Driller

Yield: 30 gal./min. with 55 ft. drawdown after 5 hrs.

" " "

" " "

Bailer test gal./min. with ft. drawdown after hrs.

Artesian flow g.p.m.

Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION:

Well seal—Material used Cement

Well sealed from land surface to 30 ft.

Diameter of well bore to bottom of seal 10 in.

Diameter of well bore below seal 10 in.

Number of sacks of cement used in well seal 15 sacks

Number of sacks of bentonite used in well seal 0 sacks

Brand name of bentonite

Number of pounds of bentonite per 100 gallons of water lbs./100 gals.

Was a drive shoe used? ☑ Yes ☐ No Plugs Size: location ft.

Did any strata contain unusable water? ☐ Yes ☑ No

Type of water? depth of strata

Method of sealing strata off

Was well gravel packed? ☑ Yes ☐ No Size of gravel: 3/8-R

Gravel placed from 30 ft. to 91 ft.

(10) LOCATION OF WELL:

County Yamhill Driller's well number 278

¼ ¼ Section 32 T. 4S R. 4W W.M.

Bearing and distance from section or subdivision corner

(11) WATER LEVEL: Completed well.

Depth at which water was first found 70 ft.

Static level 30 ft. below land surface. Date 9-27-73

Artesian pressure lbs. per square inch. Date

(12) WELL LOG:

Diameter of well below casing 0

Depth drilled 91 ft. Depth of completed well 91 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. *Report each change in position of Static Water Level and indicate principal water-bearing strata.*

MATERIAL	From	To	SWL
Top Soil	0	2	
Brown Clay	2	25	
Blue Clay	25	70	
Sand (Black)	70	75	30
Blue Clay + Gravel (Med)	75	91	30

Work started 9-24 1973 Completed 9-26 1973

Date well drilling machine moved off of well 9-26 1973

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] William R. Kuhnhausen (Drilling Machine Operator) Date 9-27, 1973

Drilling Machine Operator's License No. 639

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

Name Blue Water Drilling Co (Person, firm or corporation) (Type or print)

Address P.O. Box 75 Dayton Ore

[Signed] Robert E. Kuhnhausen (Water Well Contractor)

Contractor's License No. 417 Date Oct 6, 1973

(USE ADDITIONAL SHEETS IF NECESSARY)

SP*45656-119