NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

(1) OWNER:

STATE OF ORLGON JUL 251973 State Well No.

(Please type or STATE ENGINEER Permit No.
(Do not write above this Inc.) EM OREGON

(10) LOCATION OF WELL:

Name LARRY V KNUTZ	County YAMHTLL Driller's well nu	ımber	
Address Rt 1 Box 159	14 14 Section 36 T48	R. 4w W.M.	
McMinville, Oregon	Bearing and distance from section or subdivision corner		
(2) TYPE OF WORK (check):	Dearing and distance from beston of basaryas		
New Well Deepening Reconditioning Abandon			
If abandonment, describe material and procedure in Item 12.	(11) WATER I EVEL Completed	-11	
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL: Completed well.		
	Depth at which water was first found it.		
Rotary Driven Domestic Domestic Municipal Domestic Domest	Static level 42 ft. below land surface. Date 7/11/73		
Dug	Artesian pressure lbs. per squar	e inch. Date	
CASING INSTALLED: Threaded Welded	(40) YVIII I I O C	-	
Threaded Welded Threaded Threa	(12) WELL LOG: Diameter of well below casing		
"Diam from ft. to ft. Gage	Depth drilled 165 ft. Depth of compl	eted well 165 ft.	
"Diam. from ft. to ft. Gage	Formation: Describe color, texture, grain size a		
Diant. Hom. It. W	and show thickness and nature of each stratur with at least one entry for each change of format		
PERFORATIONS: Perforated? ★ Yes □ No.	position of Static Water Level and indicate prin	cipal water-bearing strata.	
Type of perforator used torch	MATERIAL	From To SWL	
Size of perforations $\frac{1}{4}$ in. by 6 in.	top soil	01 31	
120 perforations from 141 ft. to 161 ft.	light yellow clay	3 27	
perforations from	light gray clay	27 38	
perforations from ft. to ft.	blue clay	38 68	
percentage and the second seco	black sand	68 73	
(7) SCREENS: Well screen installed? Yes No	blue clay	73 112	
Manufacturer's Name	send & gravel	11 2 11-9	
Type Model No	blue clay	119 124	
Diam. Slot size Set from ft. to ft.	small gravel	124 128	
Diam. Slot size Set from ft. to ft.	blue clay	128 143	
(8) WELL TESTS: Drawdown is amount water level is	small gravel	143 148	
lowered below static level	blue clay	148 159	
Was a pump test made? ☐ Yes → No If yes, by whom?	small gravel	159 162	
Yield: gal./min. with ft. drawdown after hrs.	blue clay	162 165	
, , , , , , , , , , , , , , , , , , , ,			
" " " "			
Bailer test 200 gal./min. with 118 ft. drawdown after 1 hrs.			
rtesian flow g.p.m.			
		17/44/77 10	
nperature of water Depth artesian flow encountered ft.	Work started 7/21/73 19 Complete	0/44/07	
(9) CONSTRUCTION:	Date well drilling machine moved off of well	7/11/75 19	
Well seal-Material used cement grout	Drilling Machine Operator's Certification:		
Well sealed from land surface to	This well was constructed under my		
Diameter of well bore to bottom of seal12 in.	Materials used and information reported above are true to my best knowledge and belief		
Diameter of well bore below seal8 in.	[Signed] Machine Operator) Date 7/20/73, 19		
Number of sacks of cement used in well seal20 sacks	Drilling Machine Operator's License No.		
Number of sacks of bentonite used in well seal sacks	Drilling Machine Operator's License No.		
Brand name of bentonite	Water Well Contractor's Certification:		
Number of pounds of bentonite per 100 gallons			
of water	This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.		
Was a drive shoe used? ■ Yes □ No Plugs Size: location ft.	Name CORVALLIS DRILLING CO INC		
Did any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)		
Type of water? depth of strata	Address 3440 sw 3rd; Corvallis, Ore		
Was well gravel packed? ☐ Yes 🗹 No Size of gravel:	[Signed]		
	Contractor's License No. 560 Date		
Gravel placed from ft. to ft.	Contractor's License No. 100 Date	rk-e-sek-t-t-m	