

YAMH  
52107

**RECEIVED**

APR - 5 2000

WATER RESOURCES DEPT.  
SALEM, OREGON

(1) OWNER: Well No. 1935  
Name OREGON PRIDE NURSERIES INC.  
Address 5380 SE BOOTH BEND RD  
City MCMINNVILLE St OR Zip 97128

(9) LOCATION OF WELL by legal description:  
County YAMHILL Lat. ' ' ' Long. ' ' '  
Township 4 S Range 4 W W.M.  
Section 28 SW 1/4 SE 1/4  
Tax Lot 3700 Lot Block Subdivision  
Street Address of Well (or nearest Address)  
5380 SE BOOTH BEND RD MCMINNVILLE, OR

(2) TYPE OF WORK: NEW WELL  
(3) DRILL METHOD: CABLE  
(4) PROPOSED USE: IRRIGATION

(10) STATIC WATER LEVEL:  
25 ft. below land surface. Date 04/03/70  
Artesian pressure \_\_\_\_\_ lb per square in. Date \_\_\_\_\_

(5) BORE HOLE CONSTRUCTION:  
Special Construction Approval NO Depth of Compl. Well 135 ft  
Explosives used NO Type \_\_\_\_\_ Amount \_\_\_\_\_  
HOLE SEAL  
Diam. From To Material From To Amount  
14 0 30 BENTONITE CHIP 0 30 45 SAX  
12 30 135 \_\_\_\_\_

(11) WATER BEARING ZONES:  
Depth at which water was first found 93  
From To Est Flow Rate SWL  
93 128 250 25  
\_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

Seal placement method POURED/PROBED  
Backfill: from \_\_\_\_\_ ft to \_\_\_\_\_ ft Material  
Gravel: from 30 ft to 135 ft Size 3/8" PEA

(12) WELL LOG:  
Ground elevation 155  
Material From To SWL  
TOP SOIL 0 4  
BROWN CLAY 4 17  
BLUE CLAY, DENSE 17 63  
BROWN CLAY 63 73  
BLUE CLAY, DENSE 73 93  
FINE TO MEDIUM SAND, W/FINE GRAVEL WB 93 128 25  
GREEN AND BROWN STREAKED CLAY, STICKY 128 135

(6) CASING/LINER:  
Casing Diam. From To Gauge Material Connection  
8 +1 95 .25 STEEL WELDED  
8 125 135 .25 STEEL WELDED  
2 +1 30 SCH40 PLASTIC WELDED  
Liner \_\_\_\_\_  
Final Location of shoe(s) NO SHOE, PLATE @ 135'

NOTE: 2" PVC GRAVEL FEEDER TUBE BESIDE CASING AT SURFACE TO BE USED TO MAINTAIN FILTER PACK LEVEL AT 30'.  
DAVE PAYSINGER, BLUE WATER DRILLING CO.  
(503) 868-7878  
Date started 03/14/70 Completed 04/03/70

(7) PERFORATIONS/SCREENS:  
[ ] Perf. Method \_\_\_\_\_  
[X] Screens Type JOHNSON Material STAINLESS STEEL  
Slot Tele/pipe  
From To Size Number Diam. Size Casing/liner  
95 107 110 \_\_\_\_\_ 8" PS \_\_\_\_\_ CASING  
107 125 100 \_\_\_\_\_ 8" PS \_\_\_\_\_ CASING

(unbonded) Water Well Constructor Certification: I certify that the work I performed on the construction, alteration, or abandonment of this well is in compliance with Oregon water supply well construction standards. Materials used and information reported above are true to my best knowledge and belief.  
Signed \_\_\_\_\_ WWC Number \_\_\_\_\_  
Date \_\_\_\_\_

(8) WELL TESTS: Minimum testing time is 1 hour  
Test type AIR  
Yield GPM Draw-down Drill stem at Time  
250 \_\_\_\_\_ 134 1 hr.  
250 \_\_\_\_\_ 134 23  
Temperature of water 54 Depth Artesian Flow Found \_\_\_\_\_  
Was water analysis done? NO By whom \_\_\_\_\_  
Reason for water not suitable for use \_\_\_\_\_  
Depth of strata \_\_\_\_\_

(bonded) Water Well Constructor Certification: I accept responsibility for the construction, alteration, or abandonment work performed on this well during the construction dates reported above. All work performed during this time is in compliance with Oregon water supply well construction standards. This report is true to the best of my knowledge and belief.  
Signed *David L. Paysinger* WWC Number 1438  
Date 04/03/70