

STATE OF OREGON
WATER WELL REPORT
 (as required by ORS 537.765)

PLEASE TYPE or PRINT IN INK

RECEIVED
 OCT 16 1985
 899
 WATER RESOURCES DEPT
 SALEM, OREGON
 4/3W-8
 (for official use only)

(1) OWNER:

Name John Stoller
 Address RT 2
 City DAYTON State OR

(2) TYPE OF WORK (check):

New Well Deepening Reconditioning Abandon

If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL: (4) **PROPOSED USE (check):**

Rotary Air Driven Domestic Industrial Municipal
 Thermal:
 Rotary Mud Dug Irrigation Withdrawal ReInjection
 Other:
 Cable Bored Piezometric Grounding Test

(5) CASING INSTALLED: Steel Plastic
 Threaded Welded

6" Diam. from ti ft. to 38 ft. Gauge 160#
 " Diam. from ft. to ft. Gauge

LINER INSTALLED: Steel Plastic
 Threaded Welded

4" Diam. from 0 ft. to 290 ft. Gauge 160#

(6) PERFORATIONS: Perforated? Yes No

Size of perforations 1/4 in. by 6 in.
150 perforations from 190 ft. to 290 ft.
 perforations from ft. to ft.
 perforations from ft. to ft.

(7) SCREENS: Well screen installed? Yes No

Manufacturer's Name Model No.
 Type
 Diam. Slot Size Set from ft. to ft.
 Diam. Slot Size Set from ft. to ft.

(8) WELL TESTS: Drawdown is amount water level is lowered below static level

Was a pump test made? Yes No If yes, by whom?
 gal./min. with ft. drawdown after hrs.
 Air test 13 1/2 gal./min. with drill stem at 290 ft. 1 hrs.
 Bailer test gal./min. with ft. drawdown after hrs.
 Artesian flow g.p.m.
 Temperature of water Depth artesian flow encountered ft.

(9) CONSTRUCTION: Special standards: Yes No

Well seal—Material used Cement grout
 Well sealed from land surface to 38 ft.
 Diameter of well bore to bottom of seal 8 1/2 in.
 Diameter of well bore below seal 6 in.
 Amount of sealing material 7 sacks pounds
 How was cement grout placed? pumped

Was pump installed? no Type HP Depth ft.
 Was a drive shoe used? Yes No Plugs Size: location ft.
 Did any strata contain unusable water? Yes No
 Type of Water? depth of strata
 Method of sealing strata off
 Was well gravel packed? Yes No Size of gravel:
 Gravel placed from ft. to ft.

(10) LOCATION OF WELL by legal description:

County Yamhill 1/4 1/4 of Section 8 of
 Township 45 Range 3W WM.
 (Township is North or South) (Range is East or West)
 Tax Lot Lot Block Subdivision

MAILING ADDRESS OF WELL (or nearest address)

(11) WATER LEVEL of COMPLETED WELL:

Depth at which water was first found 201 ft.
 Static level 65 ft. below land surface. Date 10-7-85
 Artesian pressure lbs. per square inch. Date

(12) WELL LOG: Diameter of well below casing 6

Depth drilled 290 ft. Depth of completed well 290 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.

MATERIAL	From	To	SWL
Top Soil	0	1	
Bottom clay	1	19	
Blue shale	19	183	
Gray shale	183	271	
Thin sand & zone	271	278	
Blue shale	278	290	

Date work started 10-4-85 /completed 10-7-85
 Date well drilling machine moved off of well 10-7 19 85

(unbonded) Water Well Constructor Certification (if applicable):

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Date, 19

(bonded) Water Well Constructor Certification:

Bond 505167 Issued by: OR egon AUTO
 (number) (Surety Company Name)
 On behalf of Robert Shelburne
 (type or print name of Water Well Constructor)

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief:

(Signed) Robert Shelburne
 (Water Well Constructor)

(Dated)

NOTICE TO WATER WELL CONSTRUCTOR
 The original and first copy of this report are to be filed with the

WATER RESOURCES DEPARTMENT,
 SALEM, OREGON 97310
 within 30 days from the date of well completion. SP*46866-690