## STATE OF OREGON

## WATER WELL REPORT

(as required by ORS 537.765)

TYPE or PRINT IN INWATER RESOURCES DEPT

RECEIVED OCT 1 6 1985 .....

	SALEM, OREGON (for official use only)
(1) OWNER:	(10) LOCATION OF WELL by legal description:
Name John & Toller	a OA was fill
Address R 2	1 V 115 311/
City Dayton State Ore	Township, Range, WM (Range is East or West)
	Tax Lot Lot Block Subdivision
(2) TYPE OF WORK (check):	MAILING ADDRESS OF WELL (or nearest address)
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐	
If abandonment, describe material and procedure in Item 12.	(41) WARRED I DIVIDE A CONTROL DESCRIPTION
(3) TYPE OF WELL: (4) PROPOSED USE (check):	(11) WATER LEVEL of COMPLETED WELL:
Rotary Air Driven Domestic Industrial Municipal Thermal:	Depth at which water was first found
Rotary Mud Dug Irrigation Withdrawal Reinjection	Static level 60 ft. below land surface. Date 10-9-1
Cable	Artesian pressure lbs. per square inch. Date
CACING INCOMALLED	(12) WELL LOG: Diameter of well below casing
(5) CASING INSTALLED: Steel	Depth drilled 2 45 ft. Depth of completed well 2 45 ft
	Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change o
	formation. Report each change in position of Static Water Level and indicate principal water-bearing strata.
LINER INSTALLED: Steel   Plastic	water-bearing strata.
Threaded Welded	MATERIAL From To SWL
——————————————————————————————————————	Jap - Sail 0/
(6) PERFORATIONS: Perforated?	Brown Clay 1 21
(6) PERFORATIONS: Perforated?	Blue Sphle 21 168
120 perforations from 16.5 ft. to 2.45 ft.	Bruy 3 halo 168 240
	700075
perforations from	·
perforations from	
(7) SCREENS: Well screen installed?   Yes No	
Manufacturer's Name	. The second
Type Model No Model No.	
Diam Slot Size Set from ft. to ft.	
Diam Slot Size Set from ft. to ft.	
(8) WELL TECTS. Drawdown is amount water level is lowered	
below static level	
Was a pump test made? ☐ Yes ☐ No If yes, by whom?	
d: gal./min. with ft. drawdown after hrs.	
и и и	
Air test 5 gal./min. with drill stem at 245ft. hrs.	
Bailer test gal./min. with ft. drawdown after hrs.	
Artesian flow g.p.m.	-
perature of water Depth artesian flow encountered ft.	1 2 2 4 20
(9) CONSTRUCTION: Special standards: Yes \( \subseteq \) No \( \subseteq \)	Date work started 10 -7 -85 /completed 10 -9 -85
Well seal—Material used Tement Grout	Date well drilling machine moved off of well 1985
Well sealed from land surface to	(unbonded) Water Well Constructor Certification (if applicable):
Diameter of well bore to bottom of seal	This well was constructed under my direct supervision. Materials used and
Diameter of well bore below seal in.	information reported above are true to my best knowledge and belief.
Amount of sealing material sacks 🖆 pounds 🗆	[Signed]
How was cement grout placed?	
7	(bonded) Water Well Constructor Certification:
	Bond SB SIG I Issued by: Olegon Holl O (Surety Company Name)
Nas pump installed?	On behalf of BOBERT Shelbarne
Was a drive shoe used? Yes Plugs Size: location ft.	(type or print name of Water Well Constructor)
Did any strata contain unusable water?    Yes  No	This well was drilled under my jurisdiction and this report is true to the
Type of Water? depth of strata	best of my knowledge and belief:
Method of sealing strata off	(Signed) Bobat Schelberry
Was well gravel packed? Yes Ano Size of gravel:	(Water Well Constructor)
Gravel placed from ft. to ft.	(Dated)/b \$5
	I and the second