

NOTICE TO WATER WELL CONTRACTOR

The original and first copy of this report are to be filed with the

STATE ENGINEER, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print) (Do not write above this line)

State Well No. 4/3w-9

State Permit No.

STATE ENGINEER SALEM, OREGON

YAMHILL 5278

(1) OWNER:

Name Wilbur Stoller Address Rt 2, Dayton

(2) TYPE OF WORK (check):

New Well [x] Deepening [] Reconditioning [] Abandon [] If abandonment, describe material and procedure in Item 12.

(3) TYPE OF WELL:

Rotary [] Cable [x] Dug [] Driven [] Jetted [] Bored []

(4) PROPOSED USE (check):

Domestic [x] Industrial [] Municipal [] Irrigation [] Test Well [] Other []

(5) CASING INSTALLED:

6 5/8" Diam. from 0 ft. to 165 ft. Gage 250 5 9/16" Diam. from 165 ft. to 200 ft. Gage 10

(6) PERFORATIONS:

Perforated? [x] Yes [] No. Type of perforator used cutting torch Size of perforations 1/4 in. by 12 in. 50 perforations from 60 ft. to 163 ft. 20 perforations from 165 ft. to 200 ft.

(7) SCREENS:

Well screen installed? [] Yes [x] No Manufacturer's Name Type Model No. Diam. Slot size Set from ft. to ft.

(8) WATER LEVEL: Completed well.

Static level 57 ft. below land surface Date NOV 27-67 Artesian pressure lbs. per square inch Date

(9) WELL TESTS:

Drawdown is amount water level is lowered below static level Was a pump test made? [] Yes [x] No If yes, by whom? Bailer test 40 gal./min. with 40 ft. drawdown after 1 hrs. Artesian flow g.p.m. Date Temperature of water Was a chemical analysis made? [] Yes [x] No

(10) CONSTRUCTION:

Well seal—Material used bentonite Depth of seal 45 ft. Diameter of well bore to bottom of seal 10 in. at 20 ft. Were any loose strata cemented off? [] Yes [x] No Depth Was a drive shoe used? [] Yes [x] No Did any strata contain unusable water? [] Yes [x] No Type of water? depth of strata Method of sealing strata off Was well gravel packed? [x] Yes [] No Size of gravel: 1/4 to 1/2 Gravel placed from 163 ft. to 45 ft.

(11) LOCATION OF WELL:

County Yamhill Driller's well number 1/4 Section 9 T. 15 R. 3 W.M.

Bearing and distance from section or subdivision corner

(12) WELL LOG:

Diameter of well below casing 5 in. Depth drilled 202 ft. Depth of completed well 202 ft.

Formation: Describe color, texture, grain size and structure of materials; and show thickness and nature of each stratum and aquifer penetrated, with at least one entry for each change of formation. Report each change in position of Static Water Level as drilling proceeds. Note drilling rates.

Table with columns: MATERIAL, From, To, SWL. Rows include: brown top soil (0-3), clay, red (3-15), rock, brown, soft (15-87, 28 ft), rock, brown, soft, broken (87-117), rock, gray, med soft, broken (117-147), rock, gray, med hard 17-18gpm (147-175, 48 ft), rock, gray, hard, broken 27gpm (175-192), rock, gray, brown, very hard broken & caving 40gpm (192-202, 57 ft)

Work started Nov 20 1967 Completed Nov 27 1967

Date well drilling machine moved off of well Nov 27 1967

Drilling Machine Operator's Certification:

This well was constructed under my direct supervision. Materials used and information reported above are true to my best knowledge and belief.

[Signed] Donald Brown Date Nov 27, 1967 (Drilling Machine Operator)

Drilling Machine Operator's License No. 453

Water Well Contractor's Certification:

This well was drilled under my jurisdiction and this report is true to the best of my knowledge and belief.

NAME JOHN MEEKER WELLDRILLING (Person, firm or corporation) (Type or print)

Address 2902 Hoover Blvd, Newberg, Ore 97132

[Signed] John H. Meeker (Water Well Contractor)

Contractor's License No. 111 Date Nov 27, 1967