ORIGINAL File Original, and Duplicate with the ATE FAICINEED STATE OF OR	THE TO MAKE TO P
SALEM, OREGON SALEM, OREGON	(10) WELL TESTS:
(1) OWNER: Oscar Dower	Was a pump test made? ☐ Yes 🕱 No If yes, by whom?
Da vton. Oregon	Yield: gal./min. with ft. draw down after hrs.
Address	1) 1) 1) 1)
	2) 2) 3) 3)
(2) LOCATION OF WELL:	Artesian flow g.p.m.
County Yarshill Owner's number, if any—	Shut-in pressure lbs. per square inch.
R. F. D. or Street No.	OBIDITESISOR 200 g.p.m. with 40 ft. drawdown
Bearing and distance from section or subdivision corner	Temperature of water Was a chemical analysis made?  Yes No
150' N from The NE corner of The	Was electric log made of well?   Yes No
Andrew SMITE DIE IN THE SWY OF SWY OF SWY	(11) WELL LOG:
	Diameter of well,inches.
(3) TYPE OF WORK (check):	Total depth 135 ft. Depth of completed well 135 ft.
'ew well Deepening Reconditioning Abandon	Formation: Describe by color character, size of material and structure, and
ibandonment, describe material and procedure in Item 11.	show thickness of aquifers and the kind and nature of the material in each stratum penetrated, with at least one entry for each change of formation.
(4) PROPOSED USE (check): (5) EQUIPMENT:	O ft. to 2 ft. Top Soil
Domestic   Industrial   Municipal   Rotary	2 " 18 " Brown Clay
I Cable II	18 " 23 " Silt
Irrigation 🛣 Test Well 🗌 Other 🔲 Dug Well 🔯	23 " 59 " Blue Clay
) CASING INSTALLED: If gravel packed	59 " 66 " Fine Sand
ireaded □ Welded 🏖	66 " 78 " Blue Clay
Gage Diameter from to	78 " 86 " Sand
FROM Oft. td. 35 ft. 8Diam. Std. Wall of Bore 2011 ft. 0 ft.	86 " 102 " Yellow & Brown Clay
Bottom	102 " 115 " Sand
" " " " " " " " " " " " " " " " " " "	115 " 123 " Clay
" " "	123 " 135 " Gravel
" " " " " " " " " " " " " " " " " " " "	11 11
" " " " Size of gravel: 111	
Describe joint	21 11
Describe John	1) 1)
(7) PERFORATIONS:	" "
Type of perforator used Torch	" "
SIZE of perforations 12 in., length, by $\frac{1}{L}$ in.	
FROM 02ft. to 115 ft. 8 perf per foot 8 No. of rows	" "
<u>"123 " 135 "                               </u>	11 23
n n n n n n n n n n n	31 10
11 11 11 11 11 11 11 11	n n
	n n
SCREENS: Give Manufacturer's Name, Model No. and Size	33
div mandador s a a a a a a a a a a a a a a a a a a	,, ,,
A CONCERNICATION.	25 73
) CONSTRUCTION:  √as a surface sanitary seal provided? ★ Yes □ No To what depth 18 ft	27 27
Were any strata sealed against pollution? ▼ Yes □ No	Ground elevation at well site feet above mean sea level.
If yes, note depth of strata	Work started May 28, 1956 Completed June 2, 1956
FROM 0 ft. to 18 ft.	Well Driller's Statement:
" "	This well was drilled under my jurisdiction and this report is
METHOD OF SEALING Cement + liquid Clark	true to the best of my knowledge and belief.
(9) WATER LEVELS:	NAME Wilcox Drilling Co.
Depth at which water was first found fi	
Standing level before perforating fi	Address P.O. Box 569 McMinnville, Ore.
Standing level after perforating 30 5 ft	Driller's well number
Log Accepted by:	[Signed] A Milland
Maria Laterala 1 100	(Well Driller)  Set of June 4, 1956
[Signed] Owner	License No. 53 Dated Suite 4, 17, 19