NOTICE TO WATER WELL CONTRACTOR
The original and first copy of this report
are to be filed with the

WATER RESOURCES DEPARTMENT, SALEM, OREGON 97310 within 30 days from the date of well completion.

WATER WELL REPORT

STATE OF OREGON

(Please type or print)
(Do not write above this line)

YAMH 5200

-			1/ \	_				
		-	11-1	ر <u>۱</u>		10		
State	Well	No.	45	121	$\omega - \omega$	17	a	Ø
				1		*****		•

State Permit No.

(1) OWNER:	(10) LOCATION OF WELL:				
Name Louis Scalvini	County /amhill Driller's well number				
Address $R + I$ Bx $I2N$	NE 14 NE, 14 Section / 9 T.45 R.3 W/ W.M.				
Dayton OR: 97/14	Bearing and distance from section or subdivision corner				
(2) TYPE OF WORK (check):					
New Well ☐ Deepening ☐ Reconditioning ☐ Abandon ☐					
If abandonment, describe material and procedure in Item 12.	(11) WATER LEVEL: Completed well.				
(3) TYPE OF WELL: (4) PROPOSED USE (check):	Depth at which water was first found /// ft.				
Rotary Driven Domestic Industrial Municipal	Static level 35 ft. below land surface. Date/0-/0-7				
☐ Bored ☐ Irrigation ☐ Test Well ☐ Other ☐	Artesian pressure lbs. per square inch. Date				
(5) CASING INSTALLED: Threaded Welded Welded Gage .2.50 " Diam. from	(12) WELL LOG: Diameter of well below casing				
Type of perforator used	MATERIAL From To SWL				
Size of perforations in. by in.	Top 50i/ 0 3				
perforations from ft. to ft.	Brown Clay 3 34				
perforations from ft. to ft.	Grey Clay 34 7/				
perforations from ft. to ft.	Sandy Blue Clay 7/ 88				
(7) SCREENS: Well screen installed? Yes No	Black Sand 88 94				
(7) SCREENS: Well screen installed? Yes No Manufacturer's Name Johnson	Sand & Small Gravel 111 121				
Type Stain less Model No.	Blue Clay 12/140				
Diam. 6.7.5. Slot size 080 Set from 110 ft. to 115 ft.					
Diam 675 Slot size 100 Set from 115 ft. to 120 ft.					
(8) WELL TESTS: Drawdown is amount water level is lowered below static level	RECEIVED				
s a pump test made? Yes No If yes, by whom?	NOV 17 1070				
gal./min. with ft. drawdown after hrs.	100 - 7 1979				
" " " "	WATER RESOURCES DEPT				
<u>"</u> "	SALEM, OREGON				
gal./min. with 87 ft. drawdown after 5 hrs.					
sian flow g.p.m.					
Temperature of water Depth artesian flow encountered ft.	Work started 10-5 1979 Completed 10-10 1979				
(9) CONSTRUCTION:	Date well drilling machine moved off of well 10-10 1979				
Well seal—Material used Cement Grout	Drilling Machine Operator's Certification:				
Well sealed from land surface toft.	This well was constructed under my direct supervision.				
Diameter of well bore to bottom of sealin.	Materials used and information reported above are true to my best knowledge and belief.				
Diameter of well bore below seal	[Signed Seith M Calmer Date 0-17, 1979				
Number of sacks of cement used in well sealsacks How was coment grout placed? PC mpcc +0	(Drilling Machine Operator) Drilling Machine Operator's License No. 1330				
bottom of annulus	and the operator's intense into				
	Water Well Contractor's Certification:				
and the second s	This well was drilled under my jurisdiction and this report is				
Was a drive shoe used? ☑ Yes 🗌 No Plugs Size: location ft.	true to the best of my knowledge and belief. Name AQUA-TECH Vell Construction Inc.				
Old any strata contain unusable water? Yes No	(Person, firm or corporation) (Type or print)				
Type of water? depth of strata	Address 868 Delta Dr. N. E. Salem				
Method of sealing strata off	[Signed] David Beach				
Was well gravel packed? Tyes No Size of gravel:	(Water Well Contractor)				
Gravel placed from ft. to ft.	Contractor's License No. 696 Date 11 1 19 79				